



LYNGDORF MH-2

AUDIOPHILE SATELLITE SPEAKER

The MH-2 is designed with a focus on discretion and exceptional performance. Available in high-gloss black or matte white, it has been designed for optimal dynamic performance combined with genuine musicality.

INCREDIBLY VERSATILE AND COMPACT

The shallow MH-2 can be placed on furniture, wall mounted, or mounted using standard aftermarket 100x100mm brackets. The cabinet is extremely compact and solid, emphasizing our focus on dynamic music reproduction without sacrificing natural timbre. The depth of the cabinet is reduced to a minimum, not only for improving the physical footprint, but also to minimize cabinet contributions.

BUILT TO PLAY LOUD

With its clear and unstressed sound, the MH-2 calls for playing loud and all night. The speaker is designed for high performance through use of a temperature resistant voice coil made from glass fibre and impregnated with polyimide resin. It features a ventilated magnet as well as a copper cap on the magnet. These measures all minimize temperature build-up and distortion.

EVEN BETTER TOGETHER

The MH-2 speakers are satellite speakers and can hold their ground on their own, but they are designed to be complemented by one or more high-end subwoofers. If you

combine them with our BW-2 high bandwidth subwoofers – along with the TDAI-2170 or TDAI-3400 with built-in RoomPerfect™ and digital crossovers – you will produce a full range system that simply outperforms anything in or above its price range.

The logistics are incredibly simple. Just hook up a pair of MH-2's and one or two BW-2's to the TDAI, switch the BW-2 to the "bypass" function, and select the preconfigured speaker setup in the TDAI's setup menu. Finish it off by running RoomPerfect™. Then sit back and enjoy.

HIGHLIGHTS

- Extremely compact and solid
- Designed for high performance
- Clear and unstressed sound
- Minimizes temperature build-up



SPECIFICATIONS

Description:	2-way speaker
Power handling:	100 W
Nominal impedance:	4 Ohm
Tweeter:	Size 1", textile soft dome, PTC protection
Midrange driver:	Size 5.25", 35 mm voice coil, cone material: aluminum, vented magnet
Frequency response:	100 to 20,000 Hz (-3dB)
Sensitivity:	87 dB (2.83V/1m)
Crossover point:	2.2 kHz
Connections:	Binding posts
Placement options:	Key hole mounting, prepared for alternative brackets
Dimensions (W x H x D):	19.0 x 24.0 x 9.5 cm 7.5 x 9.5 x 3.7 in
Weight:	3.1 kg 6.8 lb
Standard finishes:	Matte black with black fabric cover, matte white with grey fabric cover
Optional fabric covers:	Black, grey, petrol blue, dusty green, red
Item no.:	900030121, 900030122