



NX 912-SMA

PROFESSIONAL ACTIVE STAGE MONITOR



Description

NX 912-SMA speaker is a stage monitor designed for sound providers, musicians, bands, and DJs. The combination of a 1.75" compression driver, 12" woofer, two-channel 2,100W amplifier, and the TRW waveguide produces coherent 100° x 70° coverage for the listening area with up to 130dB SPL of distortion-free sound. Used as a stage monitor, stand-alone speaker system, or satellite paired with a subwoofer, the NX 912-SMA blends high performance and reliability in a compact package. Combining RCF proprietary FIRPHASE and Bass Motion Control DSP processing, NX 912-SMA Series speakers deliver absolute clarity and deep, powerful bass response. The tour-ready, rugged all-wood cabinet is easy to carry and set up on stage or on a pole.

Features

- › Up to 130 dB Sound Pressure Level
- › 2100W Class-D bi-amplification
- › 50-20000 Hz linear frequency response
- › 1.75" Compression Driver
- › 12" Woofer
- › FIRPHASE zero degrees phase technology
- › Bass Motion Control woofer excursion management
- › 70°x100° Constant Directivity Coverage Angle
- › Perfectly tailored for horizontal or vertical deployment

Part Number


13000783 NX 912-SMA	220-240 V	Black	EAN 8024530020569
13000784 NX 912-SMA	100-120 V	Black	EAN 8024530020576



NX 912-SMA

PROFESSIONAL ACTIVE STAGE MONITOR

Line Art 2D



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response	50 Hz ÷ 20000 Hz
	Max SPL @ 1m	130 dB
	Horizontal coverage angle	100°
	Vertical coverage angle	70°
Transducers	Compression Driver	1 x 1.0", 1.75" v.c
	Woofer	1 x 12", 2.5" v.c
Input/Output section	Input signal	bal/unbal
	Input connectors	Combo XLR/Jack
	Output connectors	XLR
	Input sensitivity	-2 dBu/+4 dBu
Processor section	Crossover Frequencies	1600 Hz
	Protections	Thermal, RMS
	Limiter	Soft Limiter
Power section	Total Power	2100 W Peak
	High frequencies	700 W Peak
	Low frequencies	1400 W Peak
	Cooling	Convection
	Connections	Powercon TRUE1 TOP IN/OUT
Standard compliance	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material	Plywood
	Handles	1 on side and 1 on top
	Pole mount/Cap	Yes
	Grille	Steel
	Color	Black
Size	Height	320 mm / 12.6 inches
	Width	620 mm / 24.41 inches
	Depth	394 mm / 15.51 inches
	Weight	20 kg / 44.09 lbs



NX 912-SMA

PROFESSIONAL ACTIVE STAGE MONITOR

	ACCESSORIES		
Cables	AC XLR 3M3F	13360102	8024530006402
Protections	CVR 011	13360612	8024530020958
	RP 001	13360515	8024530020460
Rigging / Mounting	AC PMX	13360232	8024530010058
	AC PRO-FS	13360109	8024530006471
	AC PRO-PM	13360110	8024530006488
	PM-KIT M20	13360067	8024530014599