



NXW 44-A

ACTIVE TWO-WAY COLUMN SPEAKER



Description

NXW 44-A is a column speaker masterfully engineered from the ground up to deliver stellar audio performance for bands, DJs, nightclubs, and rental companies. The best-in-class combination of premium RCF transducers and a 2,100W two-channel amplifier produces coherent 100° x 50° coverage for the listening area up to 135 dB SPL. The two-way design features three 10" neodymium woofers and a CMD horn-loaded 3" compression driver. The Constant Matching Design horn delivers accurate sound to the coverage area without tilting the cabinet. The speaker delivers an extended frequency range down to 45 Hz and can be used as a stand-alone speaker, flown or pole-mounted. Pairing the speaker with a subwoofer delivers full-range power for medium-sized concerts and high-powered DJ systems. Blending RCF proprietary FIRPHASE and Bass Motion Control DSP processing, the NXW 44-A speaker is tuned for absolute sound clarity and deep, powerful bass response. The rugged, tour-ready, high-quality baltic birch plywood enclosure is easy to carry and installed securely using dedicated rigging points.

Features

- › Up to 135 dB Sound Pressure Level
- › 2100W Class-D Amplifier
- › 100° x 50° Constant Directivity Coverage Angle
- › 3" Titanium Neodymium Compression Driver
- › 3 x 10" High Power Neodymium Woofers
- › 45-20000 Hz linear Frequency Response
- › Bass Motion Control and FIRPHASE processing
- › 8 x M8 Rigging Points and 8 x Quick Lock
- › IP Rated Powercon TRUE1 TOP IN/OUT

Part Number


13000805 NXW 44-A	220-240 V	Black	EAN 8024530020439
13000806 NXW 44-A	100-120 V	Black	EAN 8024530020507



NXW 44-A

ACTIVE TWO-WAY COLUMN SPEAKER

Line Art 2D



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response	45 Hz ÷ 20000 Hz
	Max SPL @ 1m	135 dB
	Horizontal coverage angle	100°
	Vertical coverage angle	50°
Transducers	Compression Driver	1 x 1.4" neo, 3.0" v.c
	Woofer	3 x 10" neo, 2.5" v.c
Input/Output section	Input signal	bal/unbal
	Input connectors	Combo XLR/Jack
	Output connectors	XLR
Processor section	Input sensitivity	-2 dBu/+4 dBu
	Crossover Frequencies	800
	Protections	Thermal, Excurs., RMS
Power section	Limiter	Soft Limiter
	Controls	Linear/Boost/High-Pass presets, Volume
	Total Power	2100 W Peak
	High frequencies	700 W Peak
Standard compliance	Low frequencies	1400 W Peak
	Cooling	Convection
	Connections	Powercon TRUE1 TOP IN/OUT
	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material	Baltic birch plywood
	Hardware	8 x M8, 8 x quick lock
	Handles	2 side
	Pole mount/Cap	Yes
Size	Grille	Steel
	Color	Black
	Height	1080 mm / 42.52 inches
	Width	297.5 mm / 11.71 inches
	Depth	373 mm / 14.69 inches
	Weight	31.55 kg / 69.56 lbs



NXW 44-A

ACTIVE TWO-WAY COLUMN SPEAKER

	ACCESSORIES		
Cables	AC XLR 3M3F	13360102	8024530006402
Protections	RP 001	13360515	8024530020460
Rigging / Mounting	AC PMX	13360232	8024530010058
	AC PRO-FS	13360109	8024530006471
	AC PRO-PM	13360110	8024530006488
	FL-B NXL 44	13360345	8024530013653
	HOIST SPACING CHAIN CH 001	13360129	8024530020774
	PM-KIT M20	13360067	8024530014599
	STCK-KIT NXL 44	13360347	8024530013646