

Technical Information

Zvezdapol Wall Paint **WHITE PRIMER**

Product description

Interior wall paint **WHITE PRIMER** based on dispersion of polymer binders, pigments, fillers and suitable additives.

Properties:

- high whiteness, low consumption,
- resistant to dry scrubbing,
- water vapor permeable,
- ecology friendly

Purpose

It can be used for all kinds of mineral surfaces, gypsum-cardboards, for walls already painted with dispersion paints.

Surface preparation

Surface should be solid, dry and clean – without any badly adhered particles, dust, oil or paint remains and other dirt. If need, level all the bumps and cracks with suitable levelling compound. Apply primer, prior to the first layer of paint. New walls should be completely dry and dust free.

Working conditions

- The optimum operating temperature is from +10°C do +30°C.
- It must not be applied at temperatures below +5°C or above +35°C and humidity higher than 80%.
- The above conditions refer to the space, the substrate and the material itself.
- High humidity and low temperatures can prolong the drying time of the material.



TOOLS CLEANING

Immediately after use, the tool should be thoroughly washed with water. If the tool is not washed immediately after use, remove hardened residues mechanically. Removal can be facilitated by immersing the tool in water for several hours.

Technical Information

Zvezdapol Wall Paint **WHITE PRIMER**

Note

THE PRODUCT MUST NOT FREEZE!

Used in a product system with:

FASAKRIL Impregnation 1:8 EXTRA

ZVEZDAPOL LEVELLING COMPOUND 3/1

ZVEZDAPOL Manual Application LEVELLING COMPOUND

ZVEZDAPOL Ready to Use LEVELLING COMPOUND

The technical data are given to achieve optimal results by using products manufactured by KANSAI HELIOS Srbija a.d. Contact our technical service for any additional information. The manufacturer reserves the right to make changes.

Instructions for application

Apply the paint in two layers using a long-fiber fur or textile paint roller. The paint needs to be stirred in can before diluting. Apply second layer only after the first one is dry. IT MUST NOT FREEZE!

Technical data

Composition:	Acrylic dispersion, mineral fillers, pigments, additives and water.
Shade:	White.
Density (g/cm ³ , 20°C):	1.47 - 1.50
Dry matter (%):	56 ± 1
pH:	7.5 – 9.5
Consumption:	120 - 180 ml/m ² of undiluted paint in two layers (consumption depends on the porosity of the substrate).
Dilution:	With water: First layer with 5-10% water. Second layer with 5-10% water.
Method of application:	Brush, roller, air spray.
Drying (t = + 20°C, rel. hum. 65%):	Apply the next layer after 4-6 h. Completely dry after 24h.
VOC:	A(a), 30 g/l; product contains: max. 30 g/l
Packaging:	Plastic packaging: 15 l
Storage and shelf life:	Originally sealed product, stored in a dry place, protected from direct sunlight and freezing (+ 5°C to + 30°C) is usable until the date indicated on the packaging.