


Grounding Clip, with Clenergy Logo

Assembly




Component





Grounding Clip, with Clenergy Logo
Part No.: EZ-GC-ST

Technical Specification

Application	For Clenergy' s PV Mounting System	
Fixing method	Fixing under clamp	
Dimensions	W34mm*L30mm*H3.7	
Weight	0.003 kg	
Packaging	1000 units per pack, 4 packs (4000 units) per carton	
Material	SUS304 1/2H	
Color	Silver	
Standard	GB50797 AS NZS1170.2-2011 EN1991 JISC8955 ASCE 7-10	

Module Inter and End Clamp, Security Series


Assembly

	
Fixing the framed panel with End Clamp	Fixing the framed panel with Inter Clamp


Component

	
End Clamp, Security Series Part No.: ER-EC-ST35/S (bar code: 13-11011-011) Part No.: ER-EC-ST40/S (bar code: 13-11011-012)	Inter Clamp, Security Series Part No.: ER-IC-ST35/S (bar code: 13-11023-001) Part No.: ER-IC-ST40/S (bar code: 13-11023-005)

Technical Specification

Application	ER-EC-ST35/S is for framed PV Module of 35-37 mm high (with ECO-Rail and T-Rail) ER-EC-ST40/S is for framed PV Module of 40-42 mm high (with ECO-Rail and T-Rail) ER-IC-ST35/S is for framed PV Module of 29-36 mm high (with ECO-Rail)/31-36 mm (with T-Rail) ER-IC-ST40/S is for framed PV Module of 34-41 mm high (with ECO-Rail)/36-41 mm (with T-Rail)	 A driving bit provided in each pack of inter clamp 
Recommended torque	16-20 N·m	
Packaging	ER-EC-ST/S: 100 units per pack, 4 packs (400 units) per carton ER-IC-ST/S: 100 units per pack, 4 packs (400 units) per carton Including a special driving bit per pack	
Packaging Dimension	L395*W260*H330mm (carton dimension)	
Weight	ER-EC-ST35/S: 0.059 Kg; 25.07 Kg (carton weight) ER-EC-ST40/S: 0.062 Kg; 26.27 Kg (carton weight) ER-IC-ST35/S: 0.075Kg; 31.47 Kg (carton weight) ER-IC-ST40/S: 0.087 Kg; 36.27 Kg (carton weight)	
Material	Main Structure: AL6005-T5 Fasteners: SUS 304	
Color	Silver (half-anodized no less than 10 μm)	
Standard	AS NZS1170.2-2011	

Mycro Rail, 380mm




Component



Mycro Rail, 380mm
Part No.: ER-R-MC/380

Technical Specification

Application	Trapezoidal Roof	
Fixing method	Fixed on the Metal roof with Self-drilling screw	
EPDM	Pre-fitted (1mm thickness)	
Dimensions	L380mm*W72mm*H21.3mm	
Weight	0.264 Kg	
Packaging	72 units per carton	
Material	Main parts: AL6005-T5 Rubber Pad: EPDM	
Color	Silver	
Finish	Anodized (no less than 10 μ m, excluding machined surfaces)	
Standard	GB50797 AS NZS1170.2-2011 EN1991 JISC8955 ASCE 7-10	