



NEXTSTEP FLOORING						Authentic - Diamonds - Originals	
		Measurement	EDGE	SURFACE	CLICK		
	 Plank						
		Different	MICRO BEVEL	EIR	Warranty domestic use		
					20 Years		
	 Herringbone						
		Different	MICRO BEVEL	EIR	Warranty domestic use		
					20 Years		
Classification requirements EN 16511							
Performance classification - Classe di Utilizzo		EN ISO 10874	class 23-31-32-33-34				
							
Wear resistance IP method A - Taber Test		ISO 24338 Procedure A		class 34			
Impact resistance		EN 13329:2006+A1:2008 Annex F		class 34			
Castor chair resistance		EN ISO 4918		class 34			
Effect of furniture leg		EN ISO 16581		Pass			
Residential indentation		EN ISO 24343-1		class 34			
Resistance to staining		EN 438-2 +A1		class 34			
Flexibility categories		EN ISO 178:2019,		Rigid			
General Requirements EN 16511							
Thickness in Total		EN 17539	4+1 and 5+1 and 5+1,5 mm				
Lenght		EN 17539	610 - 750 - 1220 - 1520 - 1820 mm				
Width		EN 17539	120 - 150 - 182 - 228 - 305 mm				
Lenght and width of squred elements		EN 17539		pass			
Squareness		EN 17539		pass			
Straightness		EN 17539		pass			
Flatness		EN 17539		pass			
General Characteristics EN 16511							
Openings		EN 17539		pass			
Height difference		EN 17539		pass			
Light fastness		EN ISO 105-B02:2014		> 6			
Dimensional stability under influence of temperature in x and y direction		TS EN ISO 23999 TS		conforme			
Curling in z direction		EN ISO 23999		d			
CE certificate EN 14041							
				conforme			
	Fire Behaviour	EN13501-1 EN 9239-1:2010		BFL-S1			
	Emission of Formaldehyde	EN 717-1:2004		E1			
	Phatalate Analysis	Inhouse Method		Phatalate Free			
	Floor Heating System	Suitable		Max.270 C			
	Thermal Resistance	EN 12667		0,0311 m2K/W			
	Thermal Conductivity	EN 12667		0.296 W/(m.K)			
	Slip Resistance	EN13893		DS			
	Electrostatic Behaviour	1815:2016		Antistatic Floor Covering			
More Technical Specification							
	Surface treatment	UV		YES			
	Thickness of wear layers	EN429		0.5mm			
	Underlay	IXPE		1,0 or 1,5 mm (kg/m3 100)			
	Weight in total	EN ISO 23997		kgs/sqm - dipende dal modello			
More VOC test							
Antibacterial		ISO22196		Pass			
		FloorScore® standard					
		Indoor Air quality Certified to SCS-EC10.3-2014 v4.1					
							
European Directive Limiting the VOC Content in Certain Products, 2004/42/EC				Pass			
Criteri Ambientali Minimi				Pass			
verified 24 Jan 2024							
made under the responsibility of Mr. Junior Antonio Lenoci - technical advisor -							

AUTHENTIC						
New Generation Flooring						
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK		
	228 X 1220	MICRO BEVEL	EIR			
	Package(m2)				Palette (m2)	Warranty(Year)
	 7 Pieces = 1.947 m ² = 19,82 kg				 64 Package = 124,62 m ² = 1.288,56 kg	20
PLANK						

DECOR	DIMENSIONS	EDGE	SURFACE	CLICK		
	150 X 750	MICRO BEVEL	EIR			
	Package(m2)				56 Palette (m2)	Warranty(Year)
	 14 Pieces = 1.575 m ² = 16,00 kg				 Package = 88,200 m ² = 916,00 kg	20
HERRINGBONE						

DIAMONDS						
New Generation Flooring						
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK		
	228 X 1220	MICRO BEVEL	EIR			
	Package(m2)				Palette (m2)	Warranty(Year)
	 7 Pieces = 1.947 m ² = 19,82 kg				 64 Package = 124,62 m ² = 1.288,56 kg	20
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK		
	150 X 750	MICRO BEVEL	EIR			
	Package(m2)				Palette (m2)	Warranty(Year)
	 14 Pieces = 1.575 m ² = 16,00 kg				 56 Package = 88,200 m ² = 916,00 kg	20

ORIGINALS				
New Generation Flooring				
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
	228 X 1220	MICRO BEVEL	EIR	
	Package(m2)	Palette (m2)	Warranty(Year)	
	 9 Pieces = 2.503 m ² = 20,38 kg	 44 Package = 110,151 ² m = 916,61 kg	20	
PLANK				

DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
	150 X 600	MICRO BEVEL	EIR	
	Package(m2)	Palette (m2)	Warranty(Year)	
	 16 Pieces = 1.444 m ² = 11,91 kg	 72 Package = 105,408 m ² = 87 7,66 kg	20	
HERRINGBONE				