


NEXTSTEP FLOORING Authentic - Diamonds - Originals					
		Measurement	EDGE	SURFACE	CLICK
	 Plank				 Warranty domestic use
		Different	MICRO BEVEL	EIR	20 Years
	 Herringbone				 Warranty domestic use
		Different	MICRO BEVEL	EIR	20 Years
Classification requirements EN 16511					
Performance classification - Classe di Ut il izzo		EN ISO 10874	class 23-31-32-33-34		
					
Wear resistance IP method A - Taber Test		ISO 24338 Procedure A		class 34	
Impact resistance		EN 13329:2006+A1:2008 Annex F		class 34	
Castor chair resistance		EN ISO 4918		class 34	
Effect of furniture leg		EN ISO 16581		Pass	
Residential indentation		EN ISO 24343-1		class 34	
Resistance to staining		EN 438-2 +A1		class 34	
Flexibility categories		EN ISO 178:2019,		Rigid	
General Requirements EN 16511					
Thickness in Total		EN 17539	4+1 and 5+1 and 5+1,5 mm		
Lenght		EN 17539	610 - 750 - 1220 - 1520 - 1820 mm		
Width		EN 17539	120 - 150 - 182 - 228 - 305 mm		
Lenght and width of squred elements		EN 17539		pass	
Squareness		EN 17539		pass	
Straightness		EN 17539		pass	
Flatness		EN 17539		pass	
General Characteristics EN 16511					
Openings		EN 17539		pass	
Height difference		EN 17539		pass	
Light fastness		EN ISO 105-B02:2014		> 6	
Dimensional stability under influence of temperature in x and y direction		TS EN ISO 23999 TS		conformed	
Curling in z direction		EN ISO 23999		conformed	
CE certificate EN 14041					
	Fire Behaviour	EN13501-1 EN 9239-1:2010	BFL-S1		
	Emission of Formaldehyde	EN 717-1:2004	E1 Phatalate		
	Phatalate Analysis	Inhouse Method	Free Max.270 C		
	Floor Heating System	Suitable	0,0311 m2K/W		
	Thermal Resistance	EN 12667			
	Thermal Conductivity	EN 12667	0.296 W/(m.K)		
	Slip Resistance	EN 51130	R9 (SUMT); R10 (WS)		
	Electrostatic Behaviour	1815:2016	Antistatic Floor Covering		
	Abrasion Resistance	ISO 24338	AC5, ≥ 6.000 Cycles		
More Technical Specification					
	Surface treatment	UV	YES		
	Thickness of wear layers	EN429	0.5mm		
	Underlay	IXPE	1,0 or 1,5 mm (kg/m3 100)		
	Weight in total	EN ISO 23997	kgs/sqm - dipende dal modello		
More VOC test					
Antibacterial		ISO22196	Pass		
		FloorScore® standard			
		Indoor Air quality Certified to SCS-EC10.3-2014 v4.1			
European Directive Limiting the VOC Content in Certain Products, 2004/42/EC		Pass			
Criteri Ambientali Minimi		Pass			
verified 24 Jan 2024					
made under the responsibility of Mr. Junior Antonio Lenoci - technical advisor -					

AUTHENTIC					
New Generation Flooring					
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK	
 PLANK	228 X 1220	MICRO BEVEL	EIR	 20	
	Package(m2)	Palette (m2)	Warranty(Year)		
	 7 Pieces = 1.947 m ² = 19,82 kg	 64 Package = 124,62 m ² = 1.288,56 kg			
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK	
 HERRINGBONE	150 X 750	MICRO BEVEL	EIR	 20	
	Package(m2)	Palette (m2)	Warranty(Year)		
	 14 Pieces = 1.575 m ² = 16,00 kg	 56 Package = 88,200 m ² = 916,00 kg			

DIAMONDS				
New Generation Flooring				
DECOR	DIMENSION	EDGE	SURFACE	CLICK
 PLANK	228 X 1220	MICRO BEVEL	EIR	 20
	Palette (m2)	Palette (m2)	Warranty(Year)	
	 7 Pieces = 1.947 m ² = 19,82 kg	 64 Package = 124,62 m ² = 1.288,56 kg		
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
 HERRINGBONE	150 X 750	MICRO BEVEL	EIR	 20
	Package(m2)	Palette (m2)	Warranty(Year)	
	 14 Pieces = 1.575 m ² = 16,00 kg	 56 Package = 88,200 m ² = 916,00 kg		

ORIGINALS					
New Generation Flooring					
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK	
	228 X 1220	MICRO BEVEL	EIR	 20	
	Package(m2)	Package(m2)	Warranty(Year)		
	 9 Pieces = 2.503 m ² = 20,38 kg	 44 Package = 110,151 m ² = 916,61 kg			
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK	
	150 X 600	MICRO BEVEL	EIR	 20	
	Package(m2)	Palette (m2)	Warranty(Year)		
	 16 Pieces = 1.444 m ² = 11,91 kg	 72 Package = 105,408 m ² = 87 7,66 kg			