


Wood - Stone					
		Measurement	EDGE	SURFACE	CLICK
	Plank				
		Different	MICRO BEVEL	Wood	Warranty domestic use
					15 Years
	Herringbone				
		Different	MICRO BEVEL	Wood	Warranty domestic use
					15 Years
	Tile				
		Different	MICRO BEVEL	Stone	Warranty domestic use
					15 Years
Classification requirements EN 16511					
Performance classification		EN ISO 10874	class 23-31-32		
					
Wear resistance IP method A - Taber Test		ISO 24338 Procedure A	class 32		
Impact resistance - Resistenza all'Impatto		EN 13329:2006+A1:2008 Annex F	class 32		
Castor chair resistance		EN ISO 4918	class 32		
Effect of furniture leg		EN ISO 16581	Pass		
Residential indentation		EN ISO 24343-1	class 32		
Resistance to staining		EN 438-2 +A1	class 34		
Flexibility categories		EN ISO 178:2019,	Rigid		
General Requirements EN 16511					
Thickness in Total		EN 17539	4+1 and 5+1 and 5+1,5 mm		
Lenght		EN 17539	610 - 750 - 1220 - 1520 - 1820 mm		
Width		EN 17539	120 - 150 - 182 - 228 - 305 mm		
Lenght and width of squred elements		EN 17539		pass	
Squareness		EN 17539		pass	
Straightness		EN 17539		pass	
Flatness		EN 17539		pass	
General Characteristics EN 16511					
Openings		EN 17539		pass	
Height difference		EN 17539		pass	
Light fastness		EN ISO 105-B02:2014		> 6	
Dimensional stability under influence of temperature in x and y direction		TS EN ISO 23999		conformed	
Curling in z direction		TS EN ISO 23999		conformed	
CE certificate EN 14041					
	Fire Behaviour	EN13501-1 EN 9239-1:2010		BFL-S1	
	Emission of Formaldehyde	EN 717-1:2004		E1	
	Phatalate Analysis	Inhouse Method		Phatalate Free	
	Floor Heating System	Suitable		Max.270 C	
	Thermal Resistance	EN 12667		0,0311 m2K/W	
	Thermal Conductivity	EN 12667		0.296 W/(m.K)	
	Slip Resistance	EN13893		DS	
	Electrostatic Behaviour	1815:2016		Antistatic Floor Covering	
More Technical Specification					
	Surface treatment	UV		YES	
	Thickness of wear layers	EN429		0.3mm	
	Underlay	IXPE		1,0 or 1,5 mm (kg/m3 100)	
	Weight in total	EN ISO 23997		kgs/sqm	
More VOC test					
Antibacterial		ISO22196		Pass	
floor score FloorScore® standard Indoor Air quality Certified to SCS-EC10.3-2014 v4.1 					
European Directive Limiting the VOC Content in Certain Products, 2004/42/EC				Pass	
Criteri Ambientali Minimi				Pass	

WOOD New Generation Flooring				
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
 PLANK	228 X 1220 X 5	MICRO BEVEL	WOOD	
	Package(m2)	Palette (m2)	Warranty (Year)	
	 9 Pieces = 2.503 m ² = 20,75 kg	 44 Package = 110,132 m ² = 945,00 kg	15	
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
 HERRINGBONE	150x750	MICRO BEVEL	WOOD	
	Package(m2)	Palette (m2)	Warranty (Year)	
	 16 Pieces = 1.800 m ² = 15,00 kg	 56 Package = 100,800 m ² = 865,00 kg	15	

STONE New Generation Flooring				
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
 STONE	305 X 610	MICRO BEVEL	WOOD- STONE	
	Package(m2)	Palette (m2)	Warranty(Year)	
	 9 Pieces = 1.674 m ² = 13,70 kg	 66 Package = 110,514 m ² = 923,91 kg	15	
DECOR	DIMENSIONS	EDGE	SURFACE	CLICK
 STONE XL	305 X 1220	MICRO BEVEL	WOOD- STONE	
	Package(m2)	Palette (m2)	Warranty(Year)	
	 6 Pieces = 2.233 m ² = 18,26 kg	 48 Package = 107,165 m ² = 896,52 kg	15	