


PARADISE
1033

SERVICE LIFE
25
лет / года
сроком службы



Article	HSPRD-510		
Dimensions	mm	1292*159*10	EN 13329
Structure	R510	Hot lamination under high pressure with embossing in register, effect of aged wood, tetralateral beveled edge	
Supporting foundation	HDF	(density 875 kg/m ³ ; +/- 20 kg/m ³)	EN 316
Locking system	TC-lock	2G	
Protection of edges	Tech-3S AquaStop	Wax treatment	According to TC 5536-001-59066253-2014
Forecasted service life	not less 25 years		
Class of usage		33	EN 13329
Resistance to abrasion		AC5	EN 13329 application E
Impact resistance		IC3	EN 13329
Resistance to contamination		≥4	EN 438-2
Resistance to cigarettes		≥4	EN 438-2
Swelling across width		≤18%	EN 13329 application G
Thickness		10 mm; +/- 0,5 mm	EN 13329
Length		1292 mm; +/- 0,5 mm	EN 13329
Width		159 mm; +/- 0,1 mm	EN 13329
Rectangularity		≤0,2 mm	EN 13329
Straightness of edges of upper layer		≤0,3 mm/m	EN 13329
Bend across width		concavity ≤0,15%; convexity ≤0,20%	EN 13329
Bend across length		concavity ≤0,5%; convexity ≤1,0%	EN 13329
Clear gaps between panels		average ≤0,15 mm; maximal ≤0,20 mm	EN 13329
Difference in height between panels		average ≤0,10 mm; maximal ≤0,15 mm	EN 13329
Durability on separation		≥1,4 N/mm ²	EN 13329
Durability on abruption		≥1,4 N/mm ²	EN 13329
Fire safety		KM 5	C-RU.ПБ.25.В.04266
Class-formaldehyde		E 1	EN 717-1
Thermal resistance (m ² K)/W		<0,10	EN12667:2001
DOP (declaration of performance)			BOD-15-12-09-01, BOD-18-0-10-01
LOGISTICS			
6 boards in pack	1,232 m ² in pack	75 packs in pallette / 92,400 m ² in pallette	8,958 kg/m ²

