



OAK HERRINGBONE



Supplier	Barlinek USA Corp.
Product number	BLC-DBE1-L05-P7R-A14130-U
Catalogue number	-
EAN Code	-

DESCRIPTION OF SURFACE LAYER*	
Classification of the surface layer according EN 13489	Free class
Classification of the surface layer according Barlinek	Country class ●●●●○
Healthy knots	Acceptable , without limit
Unhealthy knots with fillin, scattered	Acceptable, cracks up to 1-37/64" x 3-15/16" (40mmx100mm), unhealthy up to 3-11/32" ( 85mm)
Unhealthy holes from knots	Acceptable up to 1-37/64" (40 mm) in diameter
Bark pockets	Acceptable
Colour scheme of surface layer	Varied, depending on wood type
Arrangement of fibres	Varied
Flecking	Acceptable , without limit
Mineral grains	Acceptable , without limit
Sapwood	Acceptable , without limit
Filling cracks in filled	Acceptable up to 5/16" (6 mm) wide, up to 15/34" (400 mm) length
Biodegradation of surface layer	Unacceptable
* According to the EN 13489 standard, 3% of different grade than indicated is acceptable. The limits of characteristic features of the product concern the upper layer of the element. The knots' fillings, especially in case of brushed surfaces, can be characterized by gaps which a deliberate effect of this kind of decorative surface. Measurement of wood characteristics according to EN 1310 standard.	

Dimensional characteristics and acceptable deviations (consistent with standard PN-EN 13489). Dimensional characteristics and dimensional tolerances, marked at the time of leaving the manufacturer's facility, given in accordance with the type of multi-layer flooring elements.

DIMENSIONS OF AN INDIVIDUAL ELEMENT			
Actual dimensions(mm)	Actual tolerances	Nominal dimensions (inch)	Nominal tolerances
Thickness: 14	Gap (between elements) ≤ 0,2 mm	Thickness 9/16	Gap (between elements) ≤ 0,008"
Length: 725	+/-0,1%	Length: 28-5/9	+/-0,1%
Width: 130	+/- 0,2mm	Width: 5-1/8	+/- 0,008"

PACKAGE		
	Actual dimensions (mm)	Nominal dimensions (inch)
Number of boards on a pack:	7 pcs. x 725	7 pcs. x 28-5/9
Pack:	0,65 m <sup>2</sup> /pack, 64 pack/pallet = 41,6m <sup>2</sup>	7 ft <sup>2</sup> /pack, 64 pack/pallet = 448,00 ft <sup>2</sup>

Thicknesses boards measured in according with EN 13647

THICKNESSES BOARD MEASURED IN ACCORDING WITH EN 13647	
Surface layer:	Actual 2,5mm (Nominal 0,098")
Core (middle and bottom layer):	Actual 11,5mm (Nominal 0,453")



MATERIAL/APPERANCE	
Product description:	Product consists of three layers: surface layer – oak, middle and bottom layer - pine
Top layer:	One row of strips, Country grade
Finish surface Layer:	Acrylic matte lacquer, UV hardened. Gloss level (Gardner scale) 7°-11°
The connection system boards: (for each package includes instructions assembly)	Cross edge - Optilock system, transverse lock insert – HDF. Contains HDF board US EPA TSCA Title VI and CARB 2 compliant.

CHARACTERISTICS OF THE SURFACE LAYER	
Surface appearance	Yellow-brown oak wood with natural features characteristic for this kind. The floor is characterized by grain variability and varied colours. It darkens under the influence of UV rays, , four-sided microbevelled top layer, structured by brushing. Coloured product, colour: gray.
Hardness oak applied to the top layer of the board. The method according testing Janka	650-1000 kG/cm <sup>2</sup> (rating IV, hardwood)

CHARACTERISTICS/ INSTALLATION INSTRUCTIONS/ WARRANTY	
Humidity board:	7% +/- 2%
Installation on underfloor heating system:	Product designed in the system of electric and water floor heating solution. For each package includes instructions assembly. More information for assembly on the <a href="http://www.barlinek.com">www.barlinek.com</a>
Limited warranty:	30 years residential, 5 years commercial

CARE OF LACQUERED FLOORS	
<p>The engineered wood flooring should be cared for using only agents intended for this purpose. Barlinek bears no responsibility for the effects of using agents made by other manufacturers.</p> <p><b>ATTENTION:</b> Before applying any third party care product be sure to test it on a concealed area of the floor to assess whether or not there is a negative reaction of lacquer on the floorboard (for example, discoloration or peeling). Regular care of lacquer floors conceals minor wear and tear of everyday use. The greatest enemies of wooden floors are water and sand. In case of soiling of the floor, these should be carefully and gently removed.</p>	

**NOTE:** Floorboards are produced exclusively from genuine wood. Because of the natural variation in the raw material, the individual floorboards and their surface may differ in color, shade, the intensity of knots and grain pattern. Sample boards, samples, photo- graphs and merchandising brochures may not fully correspond to the actual appearance of the products. The color of the product delivered may be different from the material available at the point of sale.