

|                                                                                   |                                         |               |                  |
|-----------------------------------------------------------------------------------|-----------------------------------------|---------------|------------------|
|  | MODULO                                  | Codice        | TEC.POS.57 M.2.0 |
|                                                                                   | Declaration of performance<br>Radiators | Emissione     | 24/06/2022       |
|                                                                                   |                                         | PGE collegata | TEC.PGE.1        |
|                                                                                   |                                         | N° pagina     | Pag. 1 di 7      |

1. Unique Identification code of product-type according to the EN 442-2:2014 Annex G:

- ☐ G.1 Steel sectional radiator (vertical flow rate)  
☐ G.3 Towel radiator/horizontal water flow radiator  
☒ G.9 Multi column radiator

2. Identification of the product in compliance to article 11, paragraph 4:

| Trading name | Width [mm] | Height [mm]                                                                                                                                |
|--------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| ARDESIA      | 2-3-4-5-6  | 200-207-300-356-400-406-500-556-586-600-626-656-676-750-756-786-856-876-900-926-956-1000-1056-1200-1500-1656-1800-1856-2000-2056-2200-2500 |

*Product identification codes are positioned in the product package labels.*

3. Intended use or uses of the construction product:

*Radiators for heating emission meant for permanent installation in heating systems of domestic buildings, supplied by a remote source of hot water or steam with temperature inferior to 110°C (EN 442-1-2 2014).*

4. Name and contact address of the manufacturer:

*Cordivari Srl, Zona Industriale Pagliare - 64020 Morro D'Oro (TE)*

5. Not relevant.

6. System of assessment and verification of constancy of performance:

*System 3*

7. Notified laboratory:

*Politecnico di Milano – Dipartimento di Energia (Notified body number: 1695). They have run the tests according to standardized regulation UNI EN 442 and released us:*

- Determination of the thermal power of an heating body:

*Test report N° ENE/MRT.RES.13029/13030 /13031/13032/13033 – 06/09/2013;*

- Pressure resistance test

*Test report N° 1623 BQ 200 - 23/11/2005.*

8. Not relevant.

|                                                                                   |                                         |                      |                  |
|-----------------------------------------------------------------------------------|-----------------------------------------|----------------------|------------------|
|  | <b>MODULO</b>                           | <b>Codice</b>        | TEC.POS.57 M.2.0 |
|                                                                                   | Declaration of performance<br>Radiators | <b>Emissione</b>     | 24/06/2022       |
|                                                                                   |                                         | <b>PGE collegata</b> | TEC.PGE.1        |
|                                                                                   |                                         | <b>N° pagina</b>     | Pag. 2 di 7      |

## 9. Declared performance

| Characteristics                 | Performance                           |          |          |         |         | Standardized technical specification |
|---------------------------------|---------------------------------------|----------|----------|---------|---------|--------------------------------------|
| Fire reaction                   | A1                                    |          |          |         |         | EN 442-1 : 2014                      |
| Release of dangerous substances | No                                    |          |          |         |         |                                      |
| Max working pressure            | 10 bar                                |          |          |         |         |                                      |
| Pressure tightness              | No leakage at 1,3 x working pressure  |          |          |         |         |                                      |
| Resistance to pressure          | No leakage at 1,69 x working pressure |          |          |         |         |                                      |
| Surface temperature             | Max 110°C                             |          |          |         |         |                                      |
| Rated thermal                   | 2 Sections                            |          |          |         |         |                                      |
|                                 | Measure [mm]                          | φ 50 [W] | φ 30 [W] | Km      | n       |                                      |
|                                 | 200                                   | 16,8     | 8,6      | 0,10145 | 1,3067  |                                      |
|                                 | 207                                   | 17,5     | 9,0      | 0,10721 | 1,30253 |                                      |
|                                 | 300                                   | 25,6     | 13,5     | 0,19452 | 1,2471  |                                      |
|                                 | 356                                   | 29,8     | 15,7     | 0,21983 | 1,25489 |                                      |
|                                 | 400                                   | 33,0     | 17,3     | 0,23746 | 1,26102 |                                      |
|                                 | 406                                   | 33,4     | 17,5     | 0,23997 | 1,26185 |                                      |
|                                 | 500                                   | 40,1     | 20,9     | 0,27341 | 1,27493 |                                      |
|                                 | 556                                   | 44,0     | 22,9     | 0,29132 | 1,28273 |                                      |
|                                 | 586                                   | 46,1     | 23,9     | 0,30033 | 1,2869  |                                      |
|                                 | 600                                   | 47,1     | 24,4     | 0,3044  | 1,28885 |                                      |
|                                 | 626                                   | 48,9     | 25,3     | 0,31174 | 1,29247 |                                      |
|                                 | 656                                   | 51,0     | 26,3     | 0,31987 | 1,29664 |                                      |
|                                 | 676                                   | 52,4     | 27,0     | 0,32509 | 1,29943 |                                      |
|                                 | 750                                   | 57,6     | 29,5     | 0,3431  | 1,30973 |                                      |
|                                 | 756                                   | 58,0     | 29,7     | 0,34448 | 1,31056 |                                      |
|                                 | 786                                   | 60,1     | 30,7     | 0,35117 | 1,31474 |                                      |
|                                 | 856                                   | 65,1     | 33,1     | 0,36563 | 1,32448 |                                      |
|                                 | 876                                   | 66,5     | 33,7     | 0,36949 | 1,32726 |                                      |
|                                 | 900                                   | 68,1     | 34,5     | 0,37395 | 1,3306  |                                      |
|                                 | 926                                   | 70,0     | 35,4     | 0,38244 | 1,33164 |                                      |
|                                 | 956                                   | 72,1     | 36,5     | 0,39216 | 1,33284 |                                      |
|                                 | 1000                                  | 75,2     | 38,0     | 0,40626 | 1,3346  |                                      |
|                                 | 1056                                  | 79,2     | 40,0     | 0,42399 | 133.684 |                                      |
|                                 | 1200                                  | 89,5     | 45,1     | 0,46844 | 1,3426  |                                      |
|                                 | 1500                                  | 111,0    | 55,8     | 0,55646 | 1,3546  |                                      |
|                                 | 1656                                  | 123,1    | 61,6     | 0,61469 | 1,35469 |                                      |
|                                 | 1800                                  | 134,1    | 67,1     | 0,66945 | 1,35478 |                                      |
|                                 | 1856                                  | 138,4    | 69,3     | 0,69102 | 1,35481 |                                      |
|                                 | 2000                                  | 149,8    | 75,0     | 0,74724 | 1,35479 |                                      |
|                                 | 2056                                  | 154,2    | 77,2     | 0,7694  | 1,35493 |                                      |
| 2200                            | 165,9                                 | 83,0     | 0,82719  | 1,35502 |         |                                      |
| 2500                            | 190,9                                 | 95,5     | 0,95154  | 1,3552  |         |                                      |
| Characteristic curve            | Φ = Km x ΔT^n                         |          |          |         |         |                                      |
| Resistance against corrosion    | No > 100 h                            |          |          |         |         |                                      |
| Resistance against minor impact | Class 0                               |          |          |         |         |                                      |

| Characteristics                 | Performance                           |          |          |         |         | Standardized technical specification |
|---------------------------------|---------------------------------------|----------|----------|---------|---------|--------------------------------------|
| Fire reaction                   | A1                                    |          |          |         |         | EN 442-1 : 2014                      |
| Release of dangerous substances | No                                    |          |          |         |         |                                      |
| Max working pressure            | 10 bar                                |          |          |         |         |                                      |
| Pressure tightness              | No leakage at 1,3 x working pressure  |          |          |         |         |                                      |
| Resistance to pressure          | No leakage at 1,69 x working pressure |          |          |         |         |                                      |
| Surface temperature             | Max 110°C                             |          |          |         |         |                                      |
| Rated thermal                   | 3 Sections                            |          |          |         |         |                                      |
|                                 | Measure [mm]                          | φ 50 [W] | φ 30 [W] | Km      | n       |                                      |
|                                 | 200                                   | 24,0     | 12,2     | 0,13882 | 1,3172  |                                      |
|                                 | 207                                   | 24,8     | 12,7     | 0,14498 | 1,31408 |                                      |
|                                 | 300                                   | 34,7     | 18,1     | 0,2388  | 1,2726  |                                      |
|                                 | 356                                   | 40,5     | 21,1     | 0,27205 | 1,27906 |                                      |
|                                 | 400                                   | 45,1     | 23,4     | 0,29655 | 1,28413 |                                      |
|                                 | 406                                   | 45,7     | 23,7     | 0,29979 | 1,28483 |                                      |
|                                 | 500                                   | 55,2     | 28,5     | 0,34742 | 1,29567 |                                      |
|                                 | 556                                   | 60,9     | 31,3     | 0,37325 | 1,30213 |                                      |
|                                 | 586                                   | 63,8     | 32,8     | 0,38635 | 1,30559 |                                      |
|                                 | 600                                   | 65,2     | 33,5     | 0,3923  | 1,3072  |                                      |
|                                 | 626                                   | 67,8     | 34,7     | 0,40307 | 1,3102  |                                      |
|                                 | 656                                   | 70,8     | 36,2     | 0,41507 | 1,31366 |                                      |
|                                 | 676                                   | 72,8     | 37,2     | 0,42282 | 1,31597 |                                      |
|                                 | 750                                   | 80,0     | 40,7     | 0,44981 | 1,3245  |                                      |
|                                 | 756                                   | 80,6     | 41,0     | 0,45189 | 1,32519 |                                      |
|                                 | 786                                   | 83,6     | 42,4     | 0,46203 | 1,32865 |                                      |
|                                 | 856                                   | 90,4     | 45,7     | 0,48419 | 1,33673 |                                      |
|                                 | 876                                   | 92,3     | 46,6     | 0,49015 | 1,33903 |                                      |
|                                 | 900                                   | 94,6     | 47,7     | 0,49709 | 1,3418  |                                      |
|                                 | 926                                   | 97,2     | 48,9     | 0,50884 | 1,34253 |                                      |
|                                 | 956                                   | 100,1    | 50,4     | 0,52229 | 1,34338 |                                      |
|                                 | 1000                                  | 104,3    | 52,5     | 0,5418  | 1,34462 |                                      |
|                                 | 1056                                  | 109,5    | 55,1     | 0,56625 | 1,34619 |                                      |
|                                 | 1200                                  | 123,5    | 61,9     | 0,62735 | 1,35025 |                                      |
|                                 | 1500                                  | 152,0    | 75,9     | 0,74693 | 1,3587  |                                      |
|                                 | 1656                                  | 166,7    | 83,6     | 0,84894 | 1,34962 |                                      |
|                                 | 1800                                  | 180,2    | 90,8     | 0,94858 | 1,34124 |                                      |
|                                 | 1856                                  | 185,5    | 93,6     | 0,98882 | 1,33789 |                                      |
|                                 | 2000                                  | 199,0    | 100,9    | 1,09629 | 1,3296  |                                      |
|                                 | 2056                                  | 204,3    | 103,7    | 1,13969 | 1,32634 |                                      |
|                                 | 2200                                  | 218,0    | 111,1    | 1,25556 | 1,31796 |                                      |
|                                 | 2500                                  | 246,0    | 126,6    | 1,518   | 1,3005  |                                      |
| Characteristic curve            | Φ = Km x ΔT^n                         |          |          |         |         |                                      |
| Resistance against corrosion    | No > 100 h                            |          |          |         |         |                                      |
| Resistance against minor impact | Class 0                               |          |          |         |         |                                      |

| Characteristics                 | Performance                           |          |          |         |         | Standardized technical specification |
|---------------------------------|---------------------------------------|----------|----------|---------|---------|--------------------------------------|
| Fire reaction                   | A1                                    |          |          |         |         | EN 442-1 : 2014                      |
| Release of dangerous substances | No                                    |          |          |         |         |                                      |
| Max working pressure            | 10 bar                                |          |          |         |         |                                      |
| Pressure tightness              | No leakage at 1,3 x working pressure  |          |          |         |         |                                      |
| Resistance to pressure          | No leakage at 1,69 x working pressure |          |          |         |         |                                      |
| Surface temperature             | Max 110°C                             |          |          |         |         |                                      |
| Rated thermal                   | 4 Sections                            |          |          |         |         |                                      |
|                                 | Measure [mm]                          | φ 50 [W] | φ 30 [W] | Km      | n       |                                      |
|                                 | 200                                   | 30,8     | 15,7     | 0,17563 | 1,3211  |                                      |
|                                 | 207                                   | 32,0     | 16,3     | 0,18528 | 1,31715 |                                      |
|                                 | 300                                   | 46,5     | 24,5     | 0,33198 | 1,2647  |                                      |
|                                 | 356                                   | 54,1     | 28,2     | 0,37114 | 1,27346 |                                      |
|                                 | 400                                   | 59,8     | 31,1     | 0,39911 | 1,28035 |                                      |
|                                 | 406                                   | 60,5     | 31,5     | 0,40275 | 1,28129 |                                      |
|                                 | 500                                   | 72,4     | 37,3     | 0,4547  | 1,296   |                                      |
|                                 | 556                                   | 79,3     | 40,7     | 0,48154 | 1,30476 |                                      |
|                                 | 586                                   | 83,0     | 42,5     | 0,49479 | 1,30946 |                                      |
|                                 | 600                                   | 84,7     | 43,4     | 0,50071 | 1,31165 |                                      |
|                                 | 626                                   | 87,9     | 44,9     | 0,51129 | 1,31572 |                                      |
|                                 | 656                                   | 91,6     | 46,6     | 0,52284 | 1,32041 |                                      |
|                                 | 676                                   | 94,0     | 47,8     | 0,53017 | 1,32354 |                                      |
|                                 | 750                                   | 103,0    | 52,0     | 0,55484 | 1,33513 |                                      |
|                                 | 756                                   | 104,0    | 52,4     | 0,55667 | 1,33606 |                                      |
|                                 | 786                                   | 107,2    | 54,1     | 0,56552 | 1,34076 |                                      |
|                                 | 856                                   | 115,6    | 58,0     | 0,58404 | 1,35171 |                                      |
|                                 | 876                                   | 118,0    | 59,1     | 0,58882 | 1,35484 |                                      |
|                                 | 900                                   | 121,0    | 60,4     | 0,59426 | 1,3586  |                                      |
|                                 | 926                                   | 123,9    | 61,9     | 0,6116  | 1,35769 |                                      |
|                                 | 956                                   | 127,5    | 63,7     | 0,63174 | 1,35664 |                                      |
|                                 | 1000                                  | 133,0    | 66,4     | 0,66149 | 1,3551  |                                      |
|                                 | 1056                                  | 139,3    | 69,8     | 0,69978 | 1,35314 |                                      |
|                                 | 1200                                  | 156,2    | 78,5     | 0,80049 | 1,3481  |                                      |
|                                 | 1500                                  | 191,0    | 96,6     | 1,02184 | 1,3376  |                                      |
|                                 | 1656                                  | 209,7    | 105,5    | 1,08475 | 1,34568 |                                      |
|                                 | 1800                                  | 227,0    | 113,5    | 1,13868 | 1,35314 |                                      |
|                                 | 1856                                  | 233,3    | 116,7    | 1,15864 | 1,35604 |                                      |
|                                 | 2000                                  | 250,3    | 124,7    | 1,20751 | 1,3635  |                                      |
|                                 | 2056                                  | 256,9    | 127,8    | 1,22559 | 1,3664  |                                      |
|                                 | 2200                                  | 274,1    | 135,9    | 1,26983 | 1,37386 |                                      |
|                                 | 2500                                  | 310,0    | 152,5    | 1,35223 | 1,3894  |                                      |
| Characteristic curve            | Φ = Km x ΔT^n                         |          |          |         |         |                                      |
| Resistance against corrosion    | No > 100 h                            |          |          |         |         |                                      |
| Resistance against minor impact | Class 0                               |          |          |         |         |                                      |

| Characteristics                 | Performance                           |          |          |         |         | Standardized technical specification |
|---------------------------------|---------------------------------------|----------|----------|---------|---------|--------------------------------------|
| Fire reaction                   | A1                                    |          |          |         |         | EN 442-1 : 2014                      |
| Release of dangerous substances | No                                    |          |          |         |         |                                      |
| Max working pressure            | 10 bar                                |          |          |         |         |                                      |
| Pressure tightness              | No leakage at 1,3 x working pressure  |          |          |         |         |                                      |
| Resistance to pressure          | No leakage at 1,69 x working pressure |          |          |         |         |                                      |
| Surface temperature             | Max 110°C                             |          |          |         |         |                                      |
| Rated thermal                   | 5 Sections                            |          |          |         |         |                                      |
|                                 | Measure [mm]                          | φ 50 [W] | φ 30 [W] | Km      | n       |                                      |
|                                 | 200                                   | 38,4     | 19,5     | 0,21098 | 1,3301  |                                      |
|                                 | 207                                   | 39,7     | 20,1     | 0,21866 | 1,32937 |                                      |
|                                 | 300                                   | 56,2     | 28,8     | 0,3236  | 1,3196  |                                      |
|                                 | 356                                   | 65,4     | 33,3     | 0,37221 | 1,32143 |                                      |
|                                 | 400                                   | 72,4     | 36,8     | 0,4092  | 1,32287 |                                      |
|                                 | 406                                   | 73,3     | 37,3     | 0,41417 | 1,32306 |                                      |
|                                 | 500                                   | 87,7     | 44,6     | 0,48986 | 1,32613 |                                      |
|                                 | 556                                   | 96,2     | 48,8     | 0,53321 | 1,32796 |                                      |
|                                 | 586                                   | 100,7    | 51,1     | 0,55595 | 1,32894 |                                      |
|                                 | 600                                   | 102,7    | 52,1     | 0,56645 | 1,3294  |                                      |
|                                 | 626                                   | 106,6    | 54,0     | 0,58577 | 1,33025 |                                      |
|                                 | 656                                   | 111,0    | 56,3     | 0,60779 | 1,33123 |                                      |
|                                 | 676                                   | 114,0    | 57,7     | 0,6223  | 1,33188 |                                      |
|                                 | 750                                   | 124,8    | 63,1     | 0,67491 | 1,3343  |                                      |
|                                 | 756                                   | 125,7    | 63,6     | 0,6791  | 1,3345  |                                      |
|                                 | 786                                   | 130,0    | 65,7     | 0,69992 | 1,33548 |                                      |
|                                 | 856                                   | 140,0    | 70,7     | 0,74751 | 1,33776 |                                      |
|                                 | 876                                   | 143,0    | 72,2     | 0,76086 | 1,33842 |                                      |
|                                 | 900                                   | 146,4    | 73,9     | 0,77675 | 1,3392  |                                      |
|                                 | 926                                   | 150,1    | 75,6     | 0,78923 | 1,34153 |                                      |
|                                 | 956                                   | 154,4    | 77,7     | 0,8032  | 1,34421 |                                      |
|                                 | 1000                                  | 160,6    | 80,7     | 0,82291 | 1,34815 |                                      |
|                                 | 1056                                  | 168,5    | 84,4     | 0,8467  | 1,35316 |                                      |
|                                 | 1200                                  | 188,8    | 93,9     | 0,90162 | 1,36605 |                                      |
|                                 | 1500                                  | 230,4    | 113,1    | 0,99078 | 1,3929  |                                      |
|                                 | 1656                                  | 251,9    | 124,4    | 1,13375 | 1,38123 |                                      |
|                                 | 1800                                  | 272,0    | 134,9    | 1,27534 | 1,37046 |                                      |
|                                 | 1856                                  | 279,3    | 139,0    | 1,33303 | 1,36627 |                                      |
|                                 | 2000                                  | 299,0    | 149,6    | 1,48853 | 1,3555  |                                      |
|                                 | 2056                                  | 306,7    | 153,8    | 1,55189 | 1,35131 |                                      |
|                                 | 2200                                  | 326,4    | 164,6    | 1,72261 | 1,34054 |                                      |
|                                 | 2500                                  | 367,0    | 187,4    | 2,11716 | 1,181   |                                      |
| Characteristic curve            | Φ = Km x ΔT^n                         |          |          |         |         |                                      |
| Resistance against corrosion    | No > 100 h                            |          |          |         |         |                                      |
| Resistance against minor impact | Class 0                               |          |          |         |         |                                      |

|                                                                                   |                                         |                      |                  |
|-----------------------------------------------------------------------------------|-----------------------------------------|----------------------|------------------|
|  | <b>MODULO</b>                           | <b>Codice</b>        | TEC.POS.57 M.2.0 |
|                                                                                   | Declaration of performance<br>Radiators | <b>Emissione</b>     | 24/06/2022       |
|                                                                                   |                                         | <b>PGE collegata</b> | TEC.PGE.1        |
|                                                                                   |                                         | <b>N° pagina</b>     | Pag. 6 di 7      |

| Characteristics                 | Performance                           |          |          |         |         | Standardized technical specification |
|---------------------------------|---------------------------------------|----------|----------|---------|---------|--------------------------------------|
| Fire reaction                   | A1                                    |          |          |         |         | EN 442-1 : 2014                      |
| Release of dangerous substances | No                                    |          |          |         |         |                                      |
| Max working pressure            | 10 bar                                |          |          |         |         |                                      |
| Pressure tightness              | No leakage at 1,3 x working pressure  |          |          |         |         |                                      |
| Resistance to pressure          | No leakage at 1,69 x working pressure |          |          |         |         |                                      |
| Surface temperature             | Max 110°C                             |          |          |         |         |                                      |
| Rated thermal                   | 6 Sections                            |          |          |         |         |                                      |
|                                 | Measure [mm]                          | φ 50 [W] | φ 30 [W] | Km      | n       |                                      |
|                                 | 200                                   | 47,2     | 24,1     | 0,27283 | 1,3172  |                                      |
|                                 | 207                                   | 48,7     | 24,8     | 0,28099 | 1,31752 |                                      |
|                                 | 300                                   | 67,7     | 34,5     | 0,38442 | 1,3218  |                                      |
|                                 | 356                                   | 78,8     | 40,2     | 0,45566 | 1,31706 |                                      |
|                                 | 400                                   | 87,3     | 44,6     | 0,51241 | 1,31333 |                                      |
|                                 | 406                                   | 88,4     | 45,2     | 0,5202  | 1,31283 |                                      |
|                                 | 500                                   | 106,0    | 54,5     | 0,64426 | 1,30487 |                                      |
|                                 | 556                                   | 116,5    | 60,0     | 0,72005 | 1,30013 |                                      |
|                                 | 586                                   | 121,9    | 62,8     | 0,76127 | 1,29759 |                                      |
|                                 | 600                                   | 124,0    | 64,2     | 0,78066 | 1,2964  |                                      |
|                                 | 626                                   | 129,1    | 66,7     | 0,81694 | 1,2942  |                                      |
|                                 | 656                                   | 134,0    | 69,5     | 0,85923 | 1,29166 |                                      |
|                                 | 676                                   | 138,0    | 71,4     | 0,8877  | 1,28997 |                                      |
|                                 | 750                                   | 151,0    | 78,3     | 0,99491 | 1,2837  |                                      |
|                                 | 756                                   | 152,0    | 78,9     | 1,00374 | 1,28319 |                                      |
|                                 | 786                                   | 157,1    | 81,7     | 1,04819 | 1,28065 |                                      |
|                                 | 856                                   | 169,0    | 88,1     | 1,15396 | 1,27473 |                                      |
|                                 | 876                                   | 172,4    | 90,0     | 1,18473 | 1,27303 |                                      |
|                                 | 900                                   | 176,4    | 92,1     | 1,22197 | 1,271   |                                      |
|                                 | 926                                   | 180,7    | 94,1     | 1,22104 | 1,27738 |                                      |
|                                 | 956                                   | 185,7    | 96,3     | 1,21889 | 1,28474 |                                      |
|                                 | 1000                                  | 193,0    | 99,5     | 1,2138  | 1,29553 |                                      |
|                                 | 1056                                  | 201,9    | 103,4    | 1,20433 | 1,30927 |                                      |
|                                 | 1200                                  | 225,0    | 113,1    | 1,16725 | 1,3446  |                                      |
|                                 | 1500                                  | 270,0    | 130,8    | 1,05173 | 1,4182  |                                      |
|                                 | 1656                                  | 292,5    | 142,6    | 1,19116 | 1,40684 |                                      |
|                                 | 1800                                  | 313,0    | 153,2    | 1,32663 | 1,39636 |                                      |
|                                 | 1856                                  | 320,4    | 157,3    | 1,38115 | 1,39228 |                                      |
|                                 | 2000                                  | 340,0    | 167,8    | 1,52623 | 1,3818  |                                      |
|                                 | 2056                                  | 347,2    | 171,8    | 1,5461  | 1,37772 |                                      |
|                                 | 2200                                  | 366,0    | 182,0    | 1,73995 | 1,36724 |                                      |
|                                 | 2500                                  | 403,0    | 202,9    | 2,08914 | 1,3454  |                                      |
| Characteristic curve            | Φ = Km x ΔT^n                         |          |          |         |         |                                      |
| Resistance against corrosion    | No > 100 h                            |          |          |         |         |                                      |
| Resistance against minor impact | Class 0                               |          |          |         |         |                                      |

|                                                                                   |                                         |               |                  |
|-----------------------------------------------------------------------------------|-----------------------------------------|---------------|------------------|
|  | MODULO                                  | Codice        | TEC.POS.57 M.2.0 |
|                                                                                   | Declaration of performance<br>Radiators | Emissione     | 24/06/2022       |
|                                                                                   |                                         | PGE collegata | TEC.PGE.1        |
|                                                                                   |                                         | N° pagina     | Pag. 7 di 7      |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. Present declaration is released under exclusive responsibility of the Manufacturer in accordance to point 4.

Morro D'Oro, Rev.01 21/01/2020

C.E.O

Ercole Cordivari

