

DECLARATION OF PERFORMANCE
according to Regulation (EC) 305/2011
No. 2015 - 10 - 0007

- 1 Unique identification code of the product-type: Room heaters fired by wood fuel without hot water supply „AQUAS 22“
- 2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): Serial No (see rating label on the product): 00040
- 3 Intended use or use of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Appliance with intermittent and continues burning regime for operation with closed doors
- 4 Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): **TIM SISTEM d.o.o.**
Prva Berbernička str.No.9, Industrial area Nova Pazova
22 330 Nova Pazova, Serbia, e-mail: office@timsistem.rs
- 5 Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): -
- 6 System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
- 7 In case of the declaration of performance concerning a construction product covered by a harmonized standard: **KONTROL 94 Ltd**
2 Mladost str. 5100 Gorna Oryahovitsa, Republic of Bulgaria,
Body ID : 1879 , Test report :NB 1879-K-07-2015-C
8. Declared performance:

Harmonized technical specification	EN 14785:2006 , CEN/TS 15883:2009
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distance, in mm sides = 200, rear = 300, front = 800
Risk of burning fuel falling out	Pass
Emission of combustion products	CO [0,0048%] Dust [19,10 mg/m ³] NOx [122,79 mg/Nm ³] CxHy [- mg/m ³]
Surface temperature	Pass (operating tool)
Electrical safety	NPD
Clean ability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T [142 °C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	19,86 kW
Room heating output	2,61 kW
Water heating output	17,25 kW
Energy efficiency	η [93,77 %]

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

10.07.2015.


Ivan Stanković, CEO