

Technical Parameter		
Model (CCS, USA, GBT)	BSEC-3.5K (A) 1 () 230S , BSEC-7K (A) 1 () 230S BSEC-11K (A) 1 () 400S , BSEC-22K (A) 1 () 400S	
<b>Structure Appearance</b>		
Dimension (W/H/D)	283*115*400	283*115*1270/300*300*1450
Installation method	Wall-mounted	floor-mounted
Wiring method	Bottom line in, bottom line out	
Weight	6kg	18/50 KG
Number of Outputs	1/2 (optional)	
Output type	IEC 62196-2 Type 1&2, GB/T cable/socket	
Cable length	3.5 to 7m (optional)	
<b>Electric Parameter</b>		
Input voltage	230Vac ± 10%	400Vac ± 10%
Input frequency	50/60 Hz	
Output voltage	230Vac ± 10%	400Vac ± 10%
Rated power	3.5/7 KW	11/22 KW
Output current	1-Phase 16/32 A	3-Phase 16/32 A
<b>Feature Design</b>		
Network method	LAN/WIFI/4G (optional)	
Communication Protocol	OCPP1.6 (optional)	
LCD Display	No/2.4/4.3inch screen	
Language	English (optional)	
Start method	RFID/Button (optional)	
RCD Type	Type A (optional)	
<b>Environment Parameter</b>		
Applicable Scene	Indoor/Outdoor	
Operating temperature	-20°C ~ +60°C	
Storage temperature	-40°C ~ +70°C	
Operating humidity	≤ 95% non-condensing	
Acoustic noise	< 55dB	
Maximum altitude	Up to 2000m	
Cooling method	Air cooled	
Protection level	IP55, IP10	
<b>Safe design</b>		
Reference standard	CE & IEC 61851	



[在此处键入]

Protection design	Overvoltage, undervoltage, short circuit, overload, Earth, leakage, surge, over-temp, lightning
-------------------	---

Wenzhou Bluesky Energy Technology Co.,Ltd  
No.379 Binhai 22 Road ETDZ Wenzhou Zhejiang China  
www.evchargerchina.com

[Sales01@cnevcharger.com](mailto:Sales01@cnevcharger.com)  
[+8613736915467](tel:+8613736915467)