

# LS32 SMA A2

## Specificații



Descriere	LS32 SMA A2
Greutate	.3
Nivel	Comutatoare PV
Funcție	Comutatoare PV
Număr de poli	2
Tip	Șină DIN montată
Grup Catalog	Comutatoare cu came

## Specificații internaționale

Rated operation power at AC-3, 400 V	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as normally closed contact	0
Rated permanent current I <sub>u</sub>	32
Number of poles	2
Rated operating voltage	300 - 1000
Conditioned rated short-circuit current I <sub>q</sub>	5
Degree of protection (IP), front side	IP40
Number of auxiliary contacts as change-over contact	0
Interlockable	FALSE
Motor drive integrated	FALSE
Type of electrical connection of main circuit	Screw connection
Version as emergency stop installation	FALSE
Type of control element	Short thumb-grip
Version as main switch	TRUE
	kW
Version as safety switch	TRUE
Version as maintenance-/service switch	FALSE
Rated operation power at AC-23, 400 V	0
Rated short-time withstand current I <sub>cw</sub>	0
Colour control element	Black
Suitable for ground mounting	FALSE

Suitable for front mounting 4-hole	FALSE
Suitable for front mounting center	FALSE
Suitable for distribution board installation	TRUE
Suitable for intermediate mounting	FALSE
Max. rated operation voltage Ue AC	440
Motor drive optional	FALSE
Voltage release optional	FALSE
Device construction	Built-in device fixed built-in technique
Rated permanent current at AC-21, 400 V	32
Switching power at 400 V	0
Version as reversing switch	FALSE