


**R251D**

### Description

Ball valve, with female-female threaded connections.  
Standard port.

### Versions and product codes

Product code	Connections	Finishing	Handle type	Handle color
R251X001	G 1/4"F x G 1/4"F	Chrome plated brass	T-handle	Red
R251X002	G 3/8"F x G 3/8"F	Chrome plated brass	T-handle	Red
R251X003	G 1/2"F x G 1/2"F	Chrome plated brass	T-handle	Red
R251X004	G 3/4"F x G 3/4"F	Chrome plated brass	T-handle	Red
R251X005	G 1"F x G 1"F	Chrome plated brass	T-handle	Red
R251X006	G 1-1/4"F x G 1-1/4"F	Chrome plated brass	T-handle	Red
R251ZX001	Rc 1/4" x Rc 1/4"	Chrome plated brass	T-handle	Red
R251ZX003	Rc 1/2" x Rc 1/2"	Chrome plated brass	T-handle	Red
R251ZX004	Rc 3/4" x Rc 3/4"	Chrome plated brass	T-handle	Red
R251ZX005	Rc 1" x Rc 1"	Chrome plated brass	T-handle	Red
R251ZX006	Rc 1-1/4" x Rc 1-1/4"	Chrome plated brass	T-handle	Red

### Technical data

#### Main features and materials

- Suitable for water for heating/cooling systems, not dangerous gas and liquid hydrocarbons\*
- Standard port
- Valve made of UNI EN 12165 CW617N chrome plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Aluminium T-handle, red painted


#### Field of applications

- Min. working temperature: -20 °C with 50 % glycol solutions
- Max. working temperature with dry saturated steam: 185 °C with 1,05 MPa (10,5 bar)
- Max. working pressure at 20 °C with water and not dangerous gas: 4,2 MPa (42 bar) for 1/4", 3/8", 1/2", 3/4" 3,5 MPa (35 bar) for 1", 1-1/4"
- Temperature range with liquid hydrocarbons\*: -20÷60 °C
- Max. working pressure at 20 °C with liquid hydrocarbons\*: 1,2 MPa (12 bar)

\* Please consult Giacomini technical support, to check the compatibility of the product with the specific hydrocarbon.

### Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	Kv
R251X001	8	43	21	35	10	40	wr.17	6,6
R251X002	10	45	22	46	14	63	wr.21	6,7
R251X003	14	54	27	51	15	63	wr.25	10,2
R251X004	18	63	31	60	18	73	wr.32	18,5
R251X005	22	75	38	73	23	73	wr.39	36,3
R251X006	28	84	42	78	28	73	wr.48	73,5
R251ZX001	8	43	21	35	10	40	wr.17	6,6
R251ZX003	14	54	27	51	15	63	wr.25	10,2
R251ZX004	18	63	31	60	18	73	wr.32	18,5
R251ZX005	22	75	38	73	23	73	wr.39	36,3
R251ZX006	28	84	42	78	28	73	wr.48	73,5



### Product specifications

#### R251D - Red T-handle

Ball valve, with female-female threaded connections. Suitable for water for heating/cooling systems, not dangerous gas and liquid hydrocarbons. Valve made of UNI EN 12165 CW617N chrome plated brass. Standard port. Aluminium T-handle, red painted. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Min. working temperature: -20 °C with 50 % glycol solutions. Max. working temperature with dry saturated steam: 185 °C with 1,05 MPa (10,5 bar). Max. working pressure at 20 °C with water and not dangerous gas: 4,2 MPa (42 bar) for 1/4", 3/8", 1/2", 3/4"; 3,5 MPa (35 bar) for 1", 1-1/4". Temperature range with liquid hydrocarbons: -20÷60 °C. Max. working pressure at 20 °C with liquid hydrocarbons: 1,2 MPa (12 bar).