



98

Union elbow, taper seat, ISO/EN UA12

- Torque and notes for installation please find in "Technical Product Notes".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.

EN	Dim. (inch)	374 G (inch)	Black Code	Galvanised Code	SP	GP	b (mm)	c (mm)	z1 (mm)	s1 (mm)	s2 (mm)
•	¼	¾	770 098 102	770 098 202	0	80	61	21	11	15	28
•	¾	¾	770 098 103	770 098 203	0	40	65	25	15	20	32
•	½	1	770 098 104	770 098 204	10	50	76	28	15	25	41
•	¾	1 ¼	770 098 105	770 098 205	0	30	82	33	18	32	48
•	1	1 ½	770 098 106	770 098 206	0	20	94	38	21	38	55
•	1 ¼	2	770 098 107	770 098 207	0	10	107	45	26	48	67
•	1 ½	2 ¼	770 098 108	770 098 208	0	15	115	50	31	54	74
•	2	2 ¾	770 098 109	770 098 209	0	10	128	58	34	67	90
-	2 ½	3 ½	770 098 110	770 098 210	0	6	164	72	45	85	111
-	3	4	770 098 111	770 098 211	0	4	167	79	49	95	131

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>