



## 330 Union flat seat, ISO/EN U1

- Supplied without sealing gaskets; a and z1 include the seal thickness as per table "Sealing Gasket Dimension".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
- \* Inside hexagon

EN	Dim.	374 G	Black Code	Galvanised Code	SP	GP	a	z1	s1	s2	s3
	(inch)	(inch)					(mm)	(mm)	(mm)	(mm)	(mm)
•	¼	⅝	<b>770 330 102</b>	<b>770 330 202</b>	0	60	42	22	19	28	*10
•	⅜	¾	<b>770 330 103</b>	<b>770 330 203</b>	10	40	47	27	22	32	*12
•	½	1	<b>770 330 104</b>	<b>770 330 204</b>	10	70	48	22	26	41	26
•	¾	1 ¼	<b>770 330 105</b>	<b>770 330 205</b>	10	50	52	22	31	48	31
•	1	1 ½	<b>770 330 106</b>	<b>770 330 206</b>	0	30	59	25	38	55	38
•	1 ¼	2	<b>770 330 107</b>	<b>770 330 207</b>	0	20	65	27	48	67	48
•	1 ½	2 ¼	<b>770 330 108</b>	<b>770 330 208</b>	0	15	70	32	54	74	54
•	2	2 ¾	<b>770 330 109</b>	<b>770 330 209</b>	0	10	80	32	66	90	66
•	2 ½	3 ½	<b>770 330 110</b>	<b>770 330 210</b>	0	5	85	31	85	111	85
•	3	4	<b>770 330 111</b>	<b>770 330 211</b>	0	8	96	36	96	130	96
-	4	5	<b>770 330 112</b>	<b>770 330 212</b>	0	4	111	39	120	151	122

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>