



Watermann Polyworks GmbH

Am Stoppelkamp 1
D - 32758 Detmold

Tel. ++49 5231 70173-0
Fax. ++49 5231 70173-24

www.polyworks.eu
info@polyworks.eu

Technical Data Sheet

Weber.tec 828 DB 75

Elastic and alkali-resistant sealing tape for sealing under ceramic coatings

Composition

3 layered product made of polypropylene/ TPE

Applications

Sealing of joints and cracks in combination with sealing under tiles and natural stone coverings.

Properties

- High steam diffusion density
- Waterproof
- Crack bridging
- Alkali-resistant
- Non-rotting
- Low-emission

Technical key data

Version: 05/2019

Colour:			yellow	
Length:			10/50	m
Width:	DIN EN 1849-2		12	cm
Weight:	DIN EN 1849-2		265-325	g/m ²
Thickness:	DIN EN 1849-2		0,63-0,80	mm
CD Tensile strength:	DIN EN ISO 527-3		≥ 20	N/15mm
CD Elongation at maximum:	DIN EN ISO 527-3		≥ 150	%

Storage

Store at room temperature, protect from sun

The specifications presented here are based on experience on the current state of production and are subject to commercial tolerances. The publication of the values are based on present knowledge.

The quality of our materials is covered by product liability according to our terms of delivery and payment. Regarding special construction site conditions not contained in this product description, please contact our technical customer service. The information in this product data sheet does not release the user from their duty to exercise due care. Since the processing of our materials is beyond our control, we exclude any liability or warranty for misuse. 12/16 SJ