



Main

Range	Asfora
Product or component type	Dimmer
Device presentation	Complete product
Load type	230 V AC halogen lamp: 40...600 W 230 V AC incandescent lamp: 40...600 W Low voltage halogen lamp with ferromagnetic transformer: 40...600 W
Colour tint	Cream
Type of packing	Box

Complementary

Device mounting	Flush
Switch function	1-pole 2-way
Dimmer control	Rotary push type
Dimmer application	Inductive load Ohmic load
Protection type	Fuse protection
Associated fuse rating	6.3 A
[Ue] rated operational voltage	230 V AC 50 Hz
Connections - terminals	Pillar terminals
Number of cables	2 cable(s) 2.5 mm ²
Cable stiffness	Rigid Flexible
Wire stripping length	8 mm
Material	ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame ABS (acrylonitrile butadiene-styrene): knob
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws 53...78 mm
Height	83 mm
Width	83 mm
Depth	49 mm
Projecting depth	20 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	0.111 kg
------------	----------

Environment

Product certifications	UKR VDE FIMKO TSE GOST NEMKO SEMKO
Quality labels	CE
IP degree of protection	IP20

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------