

DECLARATION OF PERFORMANCE

031DPE-2013-06-30

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product

Dry-pressed ceramic tiles, with water absorption $E_b > 10\%$, TYPE WHITE BODY

2. Intended use (s)

For internal and external walls

3. Name or registered trade mark, and contact address of the manufacturer

CERAMICAS APARICI, S.A.
Ctra. Castellón-Alcora, km 12
12130 San Juan de Moró (Castellón) SPAIN

4. System (s) of assessment and verification of constancy of performance

System 4

5. . Name and identification number of notified laboratory, if relevant
N/A

6. Declared performances.

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire Release of dangerous substance, for: - Cadmium - Lead Tactility Bond strength/Adhesion - cementitious adhesives type C1 Thermal shock resistance Durability for: - internal uses - external uses: freeze-thaw resistance	A1 NPD (*) NPD (*) NPD (*) >0,5 N/mm ² Pass Pass Does not pass	EN 14411:2012

(*) Performance not declared

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

In San Juan de Moro (Castellón) Spain
June, 30 2013



Mr. Ricardo Aparici Edo

