

TECHNICAL FEATURES

MODEL:	CR.LUX DEVA NERO
FORMAT:	60x120
THICKNESS(mm):	10.5
DATE:	25/03/2025
CODE:	046.869.0215.09564
GROUP:	GRUPO B1a UNE-EN 14411 Anexo G / SASO GSO ISO 13006:2022 Anexo G
TILE TYPE:	GL
FINISH:	POLISHED
FAMILY:	GRES PORCELÁNICO-GRANILLA PULIDA RECTF.
NUMBER OF DESIGNS:	



TEST	RESULT
 UNE-EN ISO 10545-2 DIMENSIONAL FEATURES	COMPLIES WITH THE STANDARD
 UNE-EN ISO 10545-3 WATER ABSORPTION	<= 0,5 %
 UNE-EN ISO 10545-4 MODULUS OF RUPTURE - BREAKING STRENGTH	>1300 N
	MODULUS OF RUPTURE - BENDING STRENGTH >35 N/mm2
 UNE-EN ISO 10545-6 RESISTANCE TO DEEP ABRASION (MM3)	NOT APPLY
 UNE-EN ISO 10545-7 RESISTANCE TO SURFACE ABRASION	PEI III
 UNE-EN ISO 10545-8 LINEAR THERMAL EXPANSION	<7,0 x 10-6 °C-1
 UNE-EN ISO 10545-9 THERMAL SHOCK RESISTANCE	RESISTS
 UNE-EN ISO 10545-11 CRAZING RESISTANCE	RESISTS
 UNE-EN ISO 10545-12 FROST RESISTANCE	RESISTS
 UNE-EN ISO 10545-13 CHEMICAL RESISTANCE - AMMONIUM CHLORIDE 100 G/L	A
	CHEMICAL RESISTANCE - SODIUM HYPOCHLORITE 20 MG/L A
	CHEMICAL RESISTANCE - HYDROCHLORIC ACID 3% COMPLIES WITH THE STANDARD
	CHEMICAL RESISTANCE - CITRIC ACID 100 G/L COMPLIES WITH THE STANDARD
	CHEMICAL RESISTANCE - POTASSIUM HYDROXYDE 30 G/L COMPLIES WITH THE STANDARD
 UNE-EN ISO 10545-14 STAIN RESISTANCE - GREEN AGENT IN LIGHT OIL	5
	STAIN RESISTANCE - IODINE SOLUTION IN ALCOHOL 5
	STAIN RESISTANCE - OLIVE OIL 5

SLIP RESISTANCE

TEST		RESULT
	UNE 41901:2017 EX	SLIP RESISTANCE (PENDULUM)
	DIN 51130	CRITICAL ANGLE OF SLIP (INCLINED PLATFORM)
	DIN 51097	CRITICAL ANGLE OF SLIP. WET-LOADED BAREFOOT AREAS
	BS7976 (PTV) WET	CLASSIFICATION ACCORDING TO PENDULUM TEST VALUES (PTV) WET
	ANSI A326.3	DYNAMIC COEFFICIENT OF FRICTION (DCOF) OF RIGID FLOORS.
		-

TEST	VALOR UPEC
UPEC	UPEC CERTIFICATION
	-

Declaration of Performance:

https://www.pamesa.com/ERP/4.0/empresas/151/045/ficheros/t00030006/113/DdP_DoP_N003CPR2013.pdf

TECHNICAL DEPARTMENT
PAMESA CERÁMICA