



**Technical Characteristic KAI/KOS
FISA TEHNICA**

ODU
16.07.05(9/0)

Model "Goldie" Geometric

Internal code: 4995

Type: Ceramic Wall Tiles

Group BIII, 244x744x9 mm

Characteristics Group BIII, Annex L	Tolerance EN 14411:2016, %	Tolerance EN14411:2016, mm	Request values/Valori conform standard	Measured in KAI laboratory/Masuratori in laborator Kai	Measured in KAI laboratory/Masura tori in laborator Kai
1. Length/width Lungime/Latime, mm	±0.5/max±2mm	±1.25/±2.00	244 x 744	R 244x744	EN ISO 10545-2
2.Thickness Grosimea, mm	±10/max±0.5mm	±0.50	9.0 ± 0.50 mm	8.9 – 9.1 mm	EN ISO 10545-2
3. Straightness of sides Liniaritatea muchiei,mm	±0.3/max±1.5mm	±0.75/±1.50	±0.75/±1.50	-0.54 - +1.02 mm	EN ISO 10545-2
4. Rectangularity Rectangularitate, mm	±0.5/max±2mm	±1.25/±2.00	±1.25/±2.00	-0.73 - +1.29 mm	EN ISO 10545-2
5. Centre curvature Curbura centrala, mm	0.5/-0.3/ max 2.0/-1.5mm	2.00/-1.50	CC – 0.6 mm; CV + 1.8 mm	+1.31 - +1.57 mm	EN ISO 10545-2
6. Edge curvature Curbura laterala, mm	0.5/-0.3/ max 2.0/-1.5mm	1.25/-0.75 2.00/-1.50	CC – 0.6 mm; CV + 1.8 mm	-0.03 - +1.60 mm	EN ISO 10545-2
7. Warpage Deformarea, mm	±0.5/max ±2.0mm	±2.00	CC – 0.6 mm; CV + 1.8 mm	-0.16 - +0.88 mm	EN ISO 10545-2
8. Surface quality Calitatea suprafetei	≥95% without defects	≥95% without defects	Pass	Pass	EN ISO 10545-2
9.Water absorption Absorbtia de apa, %	Eb>10%	Eb>10%	Eb>10%	15.80 – 16.60 %	EN ISO 10545-3
10.Modulus of rupture Rezistenta mecanica, N/mm ²	≥12 N/mm ²	≥12 N/mm ²	≥12 N/mm ²	Average: 25 N/mm ²	EN ISO 10545-4
11. Breaking strength Fora de rupere, N	≥ 600N	≥ 600N	≥ 600N	Average: 1079 N	EN ISO 10545-4
12.Crazing resistance, glazed tiles/Resitenta la crapaturi pentru placi glazurate	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant	Resistant	EN ISO 10545-9
13.Resistance for household chemicals and swimming pool salts/Rezistenta la solutiile de uz casnic si saruriel de piscina	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant	Resistant	EN ISO 10545-11
14.Resistance to the low concentration acids and alkalis/Rezistenta la acizi si baze de concentratie slaba	Min class B	Min class B	Min class B	GA	EN ISO 10545-13
15. Resistance to the	Declared value	Declared value	Declared value		EN ISO 10545-13

high concentration acids and alkalis/ Rezistentă la acizi și baze de concentrație mare				GLA	
16. Stain resistance Rezistentă la patare	Declared value	Declared value	Declared value	GHA	EN ISO 10545-13
17. MOHS Rezistentă la zgariere	Min class 3	Min class 3	Min class 3	class 5	EN ISO 10545-14
18. Modulus of rupture Rezistentă mecanică, N/mm ²	Declared value	Declared value	Declared value	3.5	EN 101:1991

Date: 12.10.2023

