



**Technical Characteristic KAI/KOS
FISA TEHNICA**

ODU
16.07.05(7/0)

Model: "Evoque"
Internal code: 6126;6128
Type: Rectified Porcelain Tiles GL
Group BIa, Nominal size 600 x1200 mm

Group BIa, Nominal size 600 x1200 mm								
Characteristics/Caracteristici Group BIa, Annex G	Tolerance EN 14411:2016, %	Tolerance EN14411:2016, mm	Measured in KAI laboratory/Masuratori in laborator Kai	Testing method/Metoda de lucru				
1. Work size, mm (Length/width/Lungime /Latime)	±0.6/max±2mm	±2.00	<table><tr><td>Caliber</td><td>Size</td></tr><tr><td>8</td><td>598 x 1198</td></tr></table>	Caliber	Size	8	598 x 1198	EN ISO 10545-2
Caliber	Size							
8	598 x 1198							
2.Thickness/Grosimea, mm	±5/max±0.5mm	±0.45	9.0 ±0.4mm	EN ISO 10545-2				
3. Straightness of sides /Liniaritatea muchiei,mm	±0.5/max±1.5mm	±1.50	±0.8 mm	EN ISO 10545-2				
4. Rectangularity/ Rectangularitate, mm	±0.5/max±2mm	±2.00	±0.8 mm	EN ISO 10545-2				
5. Centre curvature/ Curbura centrala, mm	±0.5/max±2mm	±2.00	CC – 0.6 mm; CV + 1.5 mm	EN ISO 10545-2				
6 Edge curvature/ Curbura laterală, mm	±0.5/max±2mm	±2.00	CC – 0.6 mm; CV + 1.5 mm	EN ISO 10545-2				
7. Warpage /Deformarea, mm	±0.5/max±2mm	±2.00	CC – 0.6 mm; CV + 1.5 mm	EN ISO 10545-2				
8. Surface quality/ Calitatea suprafetei	≥95% without defects	≥95% without defects	Pass	EN ISO 10545-2				
9.Water absorption/ Absorbția de apa, %	≤0,5% Individual ≤0,6%	≤0,5% Individual ≤0,6%	0.08 – 0.14 %	EN ISO 10545-3				
10.Modulus of rupture /rezistența mecanică, N/mm²	≥35N/mm² individual≥32N/mm²	≥35N/mm² individual≥32N/mm²	≥35N/mm²	EN ISO 10545-4				
11. Breaking strength/ Forța de rupere, N	≥1300	≥1300	≥1300	EN ISO 10545-4				
12.Determination of surface abrasion for glazed tiles/Rezistența la abraziune	the class of abrasive resistance and the number of cycles are declared by producer	the class of abrasive resistance and the number of cycles are declared by producer	6126 – 4/ 6000 6128 – 3/ 1500	EN ISO 10545-7				
13.Crazing resistance, glazed tiles/Resistența la crapături pentru plăci glazurate	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant	EN ISO 10545-11				
14.Resistance for household chemicals and swimming pool salts/ Rezistența la soluțiile de uz casnic și sărurile de piscină	Min class B	Min class B	GA	EN ISO 10545-13				
15.Resistance to the low concentration acids and alkalis/Rezistența la acizi și baze de concentrație slabă	Declared value	Declared value	GLA	EN ISO 10545-13				

16. Resistance to the high concentration acids and alkalis/ Rezistentna la acizi si baze de concentratie mare	Declared value	Declared value	GHA	EN ISO 10545-13
17. Stain resistance/ Rezistentna la patare	Min class 3	Min class 3	class 5	EN ISO 10545-14
18. Frost resistance/ Rezistentna la inghet	Pass according to EN ISO 10545-1	Pass according to EN ISO 10545-1	Resistant	EN ISO 10545-12
19. MOHS/ Rezistentna la zgariere	Declared value	Declared value	9	EN 101:1991
20. Slipperiness/ Rezistentna la alunecare	Declared value	Declared value	PTV 36+ Dry PTV 36+ Wet	BS 7976
21. Slipperiness/ Rezistentna la alunecare	Declared value	Declared value	R10	DIN 51130

Date: 09.03.2023

QC:

