LECLARATION OF PERFORMANCE No. CES120150401KL

1.- Identification code of the product type and any other element allowing identification of the product:

Dry-pressed ceramic tiles with water absorption $3\% < Ev \le 6\%$ for internal walls and floors.

2.- Intended use:

Internal walls and floors

3.- Name or registered mark and address of the manufacturer

KTL KTL Ceramicas SLU C/ del Ferrocarril 4 12593-Moncofa (Castellón) ESPAÑA

4.- System of assessment and verification of constancy of performance (AVCP) System 4

5.- Name and identification number of notified laboratory, if relevant:

Not relevant

6.- Declared Performances:

SERIE 1		
Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	Class A1-A1 _{FL}	
Release of dangerous substance for: - Cadmium - Lead	NPD NPD	
Breaking Strength	≥ 1000 N	
Slipperiness	NPD	EN 14411:2012
Adhesion strength Cementitious adhesive type C1	≥ 0.5 N/mm²	
Thermal shock resistance	NPD	
Durability for: - Internal Use	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Moncofa, a 2/02/2021

KTL CERAMICAS S.L.U. CIF. 4-01771815 Calle dil Ferrocárril, 4 12593 Monodía (Castellón) Spain Tel. +34.954.584.659 - Fax +34.954.584.684.070 77