

CE DECLARATION OF PERFORMANCE No. CES320150401KL

1.- Identification code of the product type and any other element allowing identification of the product:

Dry-pressed ceramic tiles with water absorption $Ev \le 0.5\%$ for internal and external walls and floors.

2.- Intended use:

Internal and external walls and floors

3.- Name or registered mark and address of the manufacturer

KTL KTL Corémiene SLU

KTL Cerámicas SLU

C/ del Ferrocarril 4 12593-Moncofa (Castellón) ESPAÑA

4.- System of assessment and verification of constancy of performance (AVCP) System 4

5.- Name and identification number of notified laboratory, if relevant:

Not relevant

6.- Declared Performances:

SERIE 3		
Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	Class A1-A1 _{FL}	
Release of dangerous substance for: - Cadmium - Lead	NPD NPD	-
Breaking Strength	≥ 1300 N	
Slipperiness	NPD	EN 14411:2012
Adhesion strength Cementitious adhesive type C2	≥ 1 N/mm²	
Thermal shock resistance	Pass	
Durability for: - Internal Use - External use	Pass Pass	

The performance of the product identified previously is in conformity with the declared performance, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer indicated above.

Nules, a 11/12/2023

Signature: