

SPECIFICATIONS

Product


: PPRC Stop Valves

Color

: Green, Blue, Brown, Grey, White, Black

1- Product Dimensions

ØD (mm)	d (mm)	h (mm)	L (mm)	G"
20	19,5	41,8	65,4	1/2"
25	24,5	48,8	80,0	3/4"
32	31,5	56,5	94,0	1"
40	39,4	67,7	94,6	1.1/4"



2- Polymer Properties

PROPERTIES	CONDITION	METHOD	UNITS	TYPICAL VALUE
Melt Flow Rate	230 °C / 2,16 kg	ISO 1133	gr / 10 min.	≤ 0,5
Density	23 °C	ISO 1183	g/cm ³	0,900-0,910

3- Fittings Properties

PROPERTIES	CONDITION	METHOD	UNITS	TYPICAL VALUE
Hydrostatic Strength	20 °C / 16.0 mPa	ISO 1167	h	≥ 1
Hydrostatic Strength	95 °C / 4.3 mPa	ISO 1167	h	≥ 22
Hydrostatic Strength	95 °C / 3.8 mPa	ISO 1167	h	≥ 165
Hydrostatic Strength	95 °C / 3.5 mPa	ISO 1167	h	≥ 1000

4- Reference Standarts

EN 15874-3