


Uponor Aqua Pipe

Uponor Aqua Pipe natural PN10 S

- Operating pressure 10 bar
- Straight bars



Item no.	Dimension	L m	di mm	do mm	s mm	p bar	colour	Qty 2	Qty 1	UOM
1001206	32x4,4 6m	6	32	4,4	10	natural		1080	12	m
1033864	40x5,5 6m	6	40	5,5	10	natural		60	6	m
1033865	50x6,9 6m	6	50	6,9	10	natural		30	6	m
1023122	63x8,6 6m	6	63	8,6	10	natural		420	6	m
1033866	90x12,3 6m	6	90	12,3	10	natural			6	m

Uponor Aqua Pipe in conduit


Specification

- Pipes manufactured from peroxide cross-linked polyethylene (PE-Xa) acc. EN ISO 15875
- Application class 2 - Hot water supply
- Fire classification E according to DIN EN 13501-1.
- Conduits manufactured from high density polyethylene

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Leakage free tap water installations with possibility to exchange pipes in case of damage

Uponor Aqua Pipe natural in conduit black



Item no.	Dimension	L m	di1 mm	do mm	di mm	do1 mm	s mm	p bar	colour	Qty 2	Qty 1	UOM
1008993	16x2,2 25/20 50m	50	20	16	25	2,2	10	black		550	50	m
1008994	20x2,8 28/23 50m	50	23	20	28	2,8	10	black		400	50	m
1008995	25x3,5 34/28 50m	50	28	25	34	3,5	10	black		300	50	m