



The functional, elegant design of this seat and cover for the suspended WC (Ref. A346767..0) guarantees that it closes softly and quietly for safety and convenience, while the cover discreetly conceals the seat from view and is coupled with high quality hidden fixtures to achieve an immaculate, sleek appearance. The elegant contour of the entire WC unit, which features a lack of joints and visible fixtures, favours unprecedented hygiene standards in the bathroom space.

Supralit® surfaces ensure maximum hygiene thanks to reduced porosity and an antibacterial treatment. It also offers great resistance to chemical agents and ultraviolet light, ensuring that the product remains in perfect condition and maintains its original color over time.

The seat and cover are available in four finishes to match that of the selected WC: the smooth Glossy White adds a crisp, fresh look to the piece; Off-White offers an updated twist on a classic, elegant finish; warm Greige lends a discreet, sophisticated air; and the Nero finish adds a bold, contemporary feel.

Antibacterial material
Hinges material: Chromed brass
Shape: Round
Suitable for: Toilet

Colours and Finishes

How to obtain the reference number
Replace the “.” with the desired finish code from the list below

	004 Glossy white
	914 Off-white
	R34 Greige
	R54 Nero

Dimensions

Length: 525 mm.
Width: 388 mm.
Height: 48 mm.

Optional

A5258824.. Visible component for shower for intimate hygiene with built-in progressive mixer
A5251636.. Built-in component for shower for intimate hygiene with built-in progressive mixer
AR4 4. Fixed panel to be attached to one wall only
AR3 3. Pivot hinged door to be attached to one wall only with or Fixed panel to be attached to one wall only (Ref. AR4)
A816620... Covered toilet roll holder

Compatible with

A346767... Wall-hung WC
A8164880.. Built-in 3/6L dual capacitative flush plate 550 x 41.5 x 250 mm
A8164890.. Built-in 3/6L dual capacitative flush plate 250 x 41.5 x 200 mm.
A890090400 Duplo for wall-hung WC support frame
A8900970.. 3/6 L dual flush operating plate 259 x 11 x 169 mm.

Technical drawings







