

Cod Romstal		81AC0221
Power supply	Ph-V-Hz	220-240V,1Ph,50Hz
Rated Cooling	Btu/h	24000(7100~27120)
Cooling Power input	W	2345(160~2960)
Cooling Current	A	10.2(0.7~13.3)
Rated Heating	Btu/h	25000(5500~30000)
Heating Power input	W	2035(260~3140)
Heating Current	A	10.2(1.1~13.3)
Seasonal Cooling	kW	7,0
	W/W	6.1
		A++
Heating(Average)	kW	4.8
	W/W	4.0
		A+
		-7
Heating(Warmer)	kW	6.4
	W/W	5.0
		A++
		2
Tol		-15
Max. input consumption	W	3850
Max. current	A	17,5
Compressor		KTF235D22UMT
		ROTARY
		GMCC
	W	7650
	W	2065
	A	9.4
	ml	ESTEL OIL RB74AF/ 670ml
Indoor fan motor		ZKFP-58-8-1
		WZDK58-38G
	W	58.0
	uF	—
	r/min	1150 / 1000 / 850
Indoor coil		2.0
	mm	21x13.37
	mm	1.3
		Hydrophilic aluminum
	mm	Φ7,Inner groove tube
	mm	780x315x26.74
		4
Indoor air flow (Hi/Mi/Lo)	m3/h	980/817/662
Indoor sound pressure level (Hi/Mi/Lo/Si)	dB(A)	44.5/42/34.5/28
Indoor sound power level (Hi)	dB(A)	59
Indoor unit	mm	1040x220x327
	mm	1120x405x310
	Kg	12.3/15.8
Outdoor fan motor		ZKFN-50-8-2
	W	115
	uF	—

	r/min	850/700/550
		2.0
	mm	25.4x22
	mm	1.4
Outdoor coil		Hydrophilic aluminum
	mm	Φ9.52,Inner groove tube
	mm	730x660x44
		4
Outdoor air flow	m ³ /h	3000
Outdoor sound pressure level	dB(A)	59.5
Outdoor sound power level	dB(A)	67
	mm	845x363x702
Outdoor unit	mm	965x395x765
	Kg	51.5/54.5
		R32
Refrigerant		675
	Kg	1.6
Design pressure	MPa	4.3/1.7
	mm(inch)	Φ9.52(3/8'')/Φ15.9(5/8'')
Refrigerant piping	m	50
	m	25
Connection wiring		5*2.5(Optional)
Plug type		--
Thermostat type		Remote Control
Room temperature		17 32/0 30
		-15 50/-15 30