

1.6 Accessories


Yardy - All versions

Air'Suite filter

- **KAIRST** - Air'Suite biocide filter (supplied separately - only for versions MVP, MXP, IVP, IVF, IXP)
- **AIRST** - Air'Suite biocide filter (factory fitted - only for versions MVP, MXP, IVP, IVF, IXP)

Patented antibacterial filtration system, consisting of a filtering septum with G2 efficiency (according to EN779), activated with inorganic antimicrobial nano-particles to prevent bacterial growth in the filtering material.


Fire reaction F1 according to DIN 53 438-3.



Additional coil

- **KB4** (supplied separately)
- **4T** (factory fitted)

Additional water heating coil, in copper pipes and aluminium fins, with left or right connections, reversible on site.




Electric heater

- **KRER** (supplied separately only for vertical versions MVP, MVT, IVP, IVF)
- **RER** (factory fitted, for all versions)

Armoured electrical resistance made of aluminium complete with safety device for overtemperature, with relay for connection to control KTCV2/TCV2, KTCVR/TCVR, KTVD/ KTVDI, KCF/.

The electrical resistance (KRER) is supplied separately only for vertical versions MVP, MVT, IVP, IVF.



Model	power			
	0,5 kW	1 kW	2 kW	3 kW
Yardy EV3	15-20-24	25-30-34	40-45-48	55-58-60-74-80-88
Yardy-I EV3	20-24	30-34	45-48	60-74-80-88
YardyDUCT2	-	-	40-48	60-74-80-88
Yardy-ID2	-	-	40-48	60-74-80-88

ON/OFF electrovalves


2-way valve

Brass 2-way valves; electrothermal actuators with ON/OFF action (NC normally closed).

Power supply: 230 V

Protection rating: IP54

Total opening time: 4 minutes



- **KE2-2V** (supplied separately)
E2-2V (factory fitted)
2-way ON/OFF electrovalves for 2-pipe systems.


- **KE4-2V** (supplied separately)
E4-2V (factory fitted)
2-way ON/OFF electrovalves for 2-pipe systems.

3-way valve

3-way valves with 4 brass connections, with integrated bypass; electrothermal actuators with ON/OFF action (NC normally closed). Power Supply: 230V.

Protection rating: IP54

Total opening time: 4 minutes



- **KE2** (supplied separately)
- **E2** (factory fitted)
3-way ON/OFF electrovalve for 2-pipe systems.


- **KE4** (supplied separately)
- **E4** (factory fitted)
3-way ON/OFF electrovalve for 4-pipe systems.

- **KE2DD** (supplied separately)
- **E2DD** (factory fitted)
ON/OFF 3-way electrovalve with flexible pipes for 2-pipe systems with valve and balancing valve for vertical and horizontal versions.

- **KE4DD** (supplied separately)
- **E4DD** (factory fitted)

4-way valve

4-way on/off double electrovalve to use a fan coil with a single main coil, with 2 connections, in a 4-pipe system.



- **KE2X4** 4-way ON / OFF solenoid valves for 4-pipe system, for units with single battery (supplied separately)
- **E2X4** 4-way ON / OFF solenoid valves for 4-pipe systems, for single-battery units (factory mounted)