

Fisa tehnica

Cod Romstal: 81MD4112

MIH56GN18



Unitate interioara VRF tip split (montaj pe perete)

Detenta directa

Functii: incalzire si raciere

Refrigerant: R410A

Functii: mod silentios, desing compact, auto-cooling, sleep mode

Date tehnice

Model: MIH56GN18

Alimentare electrica: 220-240V, 50hZ, monofazat

Capacitate racire (temperatura interioara 27°C DB 19°C DB, temperatura exterioara 35°C DB): 5.6kW, 19. kBtu/h

Putere electrica absorbita mod racire (temperatura interioara 27°C DB 19°C DB, temperatura exterioara 35°C DB): 40W



Tel: 0372.123.101
Fax: 021.332.09.04



office@romstal.ro
www.romstal.ro



Sos. Vitan-Barzesti nr. 11A,
sector 4, Bucuresti

Reg. Com. J40/14205/1994 • Cod unic de înregistrare: 5990324 • Capital Social: 10.873.200 lei

Identificator Unic la Nivel European (EUID): ROONRC.J40/14205/1994

Conturi: RO53 INGB 0001 0001 4645 8915 ING Bank Bucuresti • RO88 BRDE 450S V009 7703 4500 BRD GSG SMCC

Capacitate incalzire (temperatura interioara, 20°C DB, temperatura exterioara 7°C DB, 6°C WB):
6.3kW, 21.5 kBtu/h

Putere electrica absorbita mod incalzire (temperatura interioara, 20°C DB, temperatura exterioara 7°C DB, 6°C WB): 40W

Debit de aer (trepte de viteza): 860/780/700/620/550/480/410 m3/h

Nivel presiune zgomot (pentru treptele de viteza aferente, masurat la 0.8m sub unitate):
41/39/37/35/33/31/29 dB(A)

Dimensiuni nete: 950x295x265 mm

Dimensiuni ambalaj: 1075x385x360 mm

Greutate neta/bruta: 11.5/14 kg

Refrigerant: R410A/R32

Dimetre conducte refrigerant lichid/gaz: 6.35/12.7mm

Diametru conducta drenaj: 16mm



Tel: 0372.123.101
Fax: 021.332.09.04



office@romstal.ro
www.romstal.ro



Sos. Vitan-Barzesti nr. 11A,
sector 4, Bucuresti