

# MSZ-S SERIES



## Indoor Unit



MSZ-SF15/20VA



## Outdoor Unit

For MXZ Connection Only

## Remote Controller



Type	Inverter Heat Pump						
Indoor Unit	MSZ-SF15VA		MSZ-SF20VA		MSZ-SF25VE3	MSZ-SF35VE3	
Outdoor Unit	for MXZ connection		MUZ-SF25VE	MUZ-SF25VEH	MUZ-SF35VE	MUZ-SF35VEH	
Refrigerant	R410A <sup>(1)</sup>						
Power Source	Outdoor Power supply						
Supply	Outdoor (V / Phase / Hz)						
	230/Single/50						
Cooling	Design load	kW	-	-	2.5	3.5	
	Annual electricity consumption <sup>(2)</sup>	kWh/a	-	-	116	171	
	SEER <sup>(3)</sup>		-	-	7.6	7.2	
	Capacity	Energy efficiency class		-	-	A++	A++
		Rated	kW	-	-	2.5	3.5
Heating (Average Season) <sup>(4)</sup>	Declared Capacity	kW	-	-	2.4(-10°C)	2.9(-10°C)	
	Back up heating capacity	at reference design temperature	-	-	2.4(-10°C)	2.9(-10°C)	
		at bivalent temperature	-	-	2.4(-10°C)	2.9(-10°C)	
	Annual electricity consumption <sup>(2)</sup>	at operation limit temperature	-	-	2.0(-15°C)	1.6(-20°C)	
		at operation limit temperature	-	-	0.0(-10°C)	0.0(-10°C)	
Indoor Unit	Operating Current (Max)	A	-	-	8.4	8.5	
	Input	Rated	kW	0.017	0.024	0.027	0.027
		Operating Current(Max)	A	0.17	0.19	0.2	0.3
	Dimensions	H*W*D	mm	250-760-168	250-760-168	299-798-195	299-798-195
	Weight	kg	-	7.7	10	10	10
Outdoor Unit	Air Volume (SLo-Lo-Mid-Hi-SH <sup>(5)</sup> (Dry/Wet))	Cooling	m <sup>3</sup> /min	3.5 - 3.9 - 4.6 - 5.5 - 6.4	3.5 - 3.9 - 4.6 - 5.5 - 6.9	3.2 - 4.1 - 5.6 - 7.2 - 9.1	3.2 - 4.1 - 5.6 - 7.2 - 9.1
	Sound Level (SPL)	Cooling	dB(A)	21 - 26 - 30 - 35 - 40	21 - 26 - 30 - 35 - 42	19 <sup>(6)</sup> - 24 - 30 - 36 - 42	19 <sup>(6)</sup> - 24 - 30 - 36 - 42
		Heating	dB(A)	21 - 26 - 30 - 35 - 40	21 - 26 - 30 - 35 - 42	19 <sup>(6)</sup> - 24 - 34 - 39 - 45	19 <sup>(6)</sup> - 24 - 34 - 39 - 45
	Operating Current (Max)	Cooling	A	59	60	57	57
		Heating	A	-	-	58	58
Ext. Piping	Diameter	Liquid/Gas	mm	6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52
	Max.Length	Out-In	m	-	-	20	20
		Out-In	m	-	-	12	12
	Guaranteed Operating Range (Outdoor)	Cooling	°C	-	-	-10 ~ +46	-10 ~ +46
		Heating	°C	-	-	-15 ~ +24	-15 ~ +24

(1) Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

(2) Energy consumption based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

(3) SHi: Super High

(4) SEER, SCOP and other related description are based on COMMISSION DELEGATED REGULATION (EU) No 626/2011. The temperature conditions for calculating SCOP are based on "Average Season".

(5) Please see page 47 for heating (warmer season) specifications.

(6) For single use: only 19dB(A). For multi use (MXZ): 21dB(A).