

WPF 13

PRODUCT-NO.: 232913

Place your trust in an absolute top performer

This high performing appliance is exceptionally proficient: it provides your house with a highly efficient supply of heat and hot water. What's more, you can combine it with any of our DHW cylinders. Your qualified contractor will install the appliance quickly and easily, as all key components are already fitted.

Advanced comfort control With an innovative heat pump manager, you have precise control over the comfort levels of your room climate at all times. The Touch-Wheel with easy to read display is simple and intuitive to use.



The main features

Ground source heat pump installed indoors for heating

Suitable for new build and modernisation projects

Also suitable for larger buildings

Low energy costs due to exemplary efficiency

Excellent COP through optimally matched components and high grade technology

First class DHW convenience thanks to flow temperatures of up to 65 °C



Type	WPF 04	WPF 05	WPF 07
Part no.	232909	232910	232911

Technical data

Heating output at B0/W35 (EN 14511)	4.77 kW	5.82 kW	7.50 kW
COP at B0/W35 (EN 14511)	4.50	4.80	4.84
SCOP (EN 14825)	4.925	5.325	5.325
Sound power level (EN 12102)	43 dB(A)	43 dB(A)	47 dB(A)
Max. application limit on the heating side	65 °C	65 °C	65 °C
Height	1319 mm	1319 mm	1319 mm
Width	598 mm	598 mm	598 mm
Depth	658 mm	658 mm	658 mm
Weight	142 kg	144 kg	161 kg
Rated voltage, compressor	400 V	400 V	400 V
Rated voltage, emergency/auxiliary heater	400 V	400 V	400 V
Refrigerant	R410A	R410A	R410A



Type	WPF 10	WPF 13	WPF 16
Part no.	232912	232913	232914

Technical data

Heating output at B0/W35 (EN 14511)	10.31 kW	13.21 kW	17.02 kW
COP at B0/W35 (EN 14511)	5.02	4.82	4.54
SCOP (EN 14825)	5.60	5.275	4.925
Sound power level (EN 12102)	48 dB(A)	49 dB(A)	53 dB(A)
Max. application limit on the heating side	65 °C	65 °C	65 °C
Height	1319 mm	1319 mm	1319 mm
Width	598 mm	598 mm	598 mm
Depth	658 mm	658 mm	658 mm
Weight	168 kg	171 kg	185 kg
Rated voltage, compressor	400 V	400 V	400 V
Rated voltage, emergency/auxiliary heater	400 V	400 V	400 V
Refrigerant	R410A	R410A	R410A



Type	WPF 05 S	WPF 07 S	WPF 10 S
Part no.	232922	232923	232924

Technical data

Heating output at B0/W35 (EN 14511)	5.88 kW	7.61 kW	10.31 kW
COP at B0/W35 (EN 14511)	4.78	4.75	4.76
SCOP (EN 14825)	5.225	5.30	5.20
Sound power level (EN 12102)	43 dB(A)	47 dB(A)	48 dB(A)
Max. application limit on the heating side	60 °C	60 °C	60 °C
Height	1319 mm	1319 mm	1319 mm
Width	598 mm	598 mm	598 mm
Depth	658 mm	658 mm	658 mm
Weight	144 kg	161 kg	168 kg
Rated voltage, compressor	230 V	230 V	230 V
Rated voltage, emergency/auxiliary heater	230 V	230 V	230 V
Refrigerant	R410A	R410A	R410A



Type	WPF 13 S
Part no.	232925

Technical data

Heating output at B0/W35 (EN 14511)	13.01 kW
COP at B0/W35 (EN 14511)	4.75
SCOP (EN 14825)	5.175
Sound power level (EN 12102)	49 dB(A)
Max. application limit on the heating side	60 °C
Height	1319 mm
Width	598 mm
Depth	658 mm
Weight	170 kg
Rated voltage, compressor	230 V
Rated voltage, emergency/auxiliary heater	230 V
Refrigerant	R410A

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.