




ENERG
енергия · ενέργεια



STIEBEL ELTRON

WPF 16



55 °C

35 °C



A⁺⁺

A⁺⁺⁺



53 dB



■ 20
■ 16
■ 16
kW

■ 21
■ 17
■ 17
kW



2015

811/2013

Product datasheet: Room heater to regulation (EU) no. 811/2013

		WPF 16
		232914
Manufacturer		STIEBEL ELTRON
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Energy efficiency class for central heating in moderate climates for low temperature applications		A+++
Rated heating output in moderate climates for medium temperature applications	kW	16
Rated heating output in moderate climates for low temperature applications	kW	17
Energy efficiency for central heating in moderate climates for medium temperature applications	%	134
Energy efficiency for central heating in moderate climates for low temperature applications	%	189
Energy consumption of central heating in moderate climates for medium temperature applications	kWh/a	9198
Energy consumption for central heating under moderate climatic conditions, for low temperature applications	kWh/a	7128
Sound power level internal	dB(A)	53
Rated heating output in colder climates for medium temperature applications	kW	20
Rated heating output in colder climates for low temperature applications	kW	21
Rated heating output in warmer climates for medium temperature applications	kW	16
Rated heating output in warmer climates for low temperature applications	kW	17
Energy efficiency for central heating in colder climates for medium temperature applications	%	138
Energy efficiency for central heating in colder climates for low temperature applications	%	194
Energy efficiency for central heating in warmer climates for medium temperature applications	%	133
Energy efficiency for central heating in warmer climates for low temperature applications	%	188
Energy consumption for central heating under colder climatic conditions, for medium temperature applications	kWh/a	13352
Energy consumption for central heating under colder climatic conditions, for low temperature applications	kWh/a	10274
Energy consumption for central heating under warmer climatic conditions, for medium temperature applications	kWh/a	5987
Energy consumption for central heating under warmer climatic conditions, for low temperature applications	kWh/a	4635



ENERG

енергия · ενεργεια

Y

IJA

IE

IA

STIEBEL ELTRON

WPF 16



A⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺⁺

A⁺

A

B

C


D

E

F

G

+



+



+



+



		WPF 16
		232914
Manufacturer		STIEBEL ELTRON
Energy efficiency for central heating in moderate climates for medium temperature applications	%	134
Temperature controller class		VII
Contribution of temperature controller to room heating energy efficiency	%	3,50
Room heating energy efficiency of composite system under moderate climatic conditions	%	138
Room heating energy efficiency of composite system under colder climatic conditions	%	142
Room heating energy efficiency of composite system under warmer climatic conditions	%	137
Value of differential between room heating energy efficiency under moderate climatic conditions and that under colder climatic conditions	%	4
Value of differential between room heating energy efficiency under warmer climatic conditions and that under moderate climatic conditions	%	1
Energy efficiency class for central heating in moderate climates for medium temperature applications		A++
Room heating energy efficiency class of composite system under moderate climatic conditions		A++

		WPF 16
		232914
Manufacturer		STIEBEL ELTRON
Heat source		Brine
Low temperature heat pump		-
With booster heater		x
Combi boiler with heat pump		-
Rated heating output in moderate climates for medium temperature applications	kW	16
Tj = -7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	15,90
Tj = 2 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	16,30
Tj = 7 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	16,60
Tj = 12 °C heating output, partial load range under moderate climatic conditions (Pdh)	kW	16,90
Tj = dual mode temperature under moderate climatic conditions (Pdh)	kW	15,80
Tj = operating temperature limit under moderate climatic conditions (Pdh)	kW	15,80
For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (Pdh)	kW	15,80
Tj = -7 °C COP, partial load range under moderate climatic conditions (COPd)		3,01
Tj = 2 °C COP, partial load range under moderate climatic conditions (COPd)		3,49
Tj = 7 °C COP, partial load range under moderate climatic conditions (COPd)		3,85
Tj = 12 °C COP, partial load range under moderate climatic conditions (COPd)		4,27
Tj = dual mode temperature under moderate climatic conditions (COPd)		2,89
Tj = operating temperature limit under moderate climatic conditions (COPd)		2,89
For air/water heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		2,89
Dual mode temperature (Tbiv)	°C	-10
Heating water operating temperature limit (WTOL)	°C	65
Power consumption, OFF state (Poff)	W	0,000
Power consumption, thermostat OFF state (PTO)	W	139
Standby power consumption (PSB)	W	9,000
Power consumption, operating state, with crankcase heating (PCK)	W	0,000
Booster heater heating output (PSUB)	kW	0,000
Type of energy supply, booster heater		electric
Power control		Fixed
Sound power level internal	dB(A)	53
Flow rate, heat source side	m³/h	4,20