

# Anerkennung

von Bauteilen und Systemen

# Approval

of Components and Systems



Inhaber der Anerkennung  
Holder of the Approval

Rapidrop Global Ltd.  
Rutland Business Park, Newark Road  
GB-PE15WA Peterborough

#### Die Anerkennung

umfasst nur das angegebene Bauteil/System in der zur Prüfung eingereichten Ausführung

- mit den Bestandteilen nach Anlage 1,
- dokumentiert in den technischen Unterlagen nach Anlage 2,
- zur Verwendung in den angegebenen Einrichtungen der Brandschutz- und Sicherungstechnik.

Bei der Anwendung des Gegenstandes der Anerkennung sind die Hinweise nach Anlage 3 zu beachten.

Das Zertifikat darf nur unverändert und mit sämtlichen Anlagen vervielfältigt werden. Alle Änderungen der Voraussetzungen für die Anerkennung sind der VdS-Zertifizierungsstelle - mitsamt den erforderlichen Unterlagen - unverzüglich zu übermitteln.

#### This Approval

is valid only for the specified component/system as submitted for testing

- together with the parts listed in enclosure 1
- documented in the technical documents according to enclosure 2
- for the use in the specified fire protection and security installations.

When using the subject of the approval the notes of enclosure 3 shall be observed.

This certificate may only be reproduced in its present form without any modifications including all enclosures. All changes of the underlying conditions of this approval shall be reported at once to the VdS certification body including the required documentation.

#### VdS Schadenverhütung GmbH

Zertifizierungsstelle  
Amsterdamer Str. 174  
D-50735 Köln

Ein Unternehmen des Gesamtverbandes der Deutschen Versicherungswirtschaft e.V. (GDV), durch die DAkkS akkreditiert als Zertifizierungsstelle für Produkte in den Bereichen Brandschutz und Sicherungstechnik

A company of the German Insurance Association (GDV) accredited by DAkkS as certification body for fire protection and security products

Anerkennungs-Nr. Approval No.	Anzahl der Seiten No. of pages	gültig vom (TT.MM.JJJJ) valid from (dd.mm.yyyy)	gültig bis (TT.MM.JJJJ) valid until (dd.mm.yyyy)
G 412020	4	29.07.2017	28.07.2021

Gegenstand der Anerkennung  
Subject of the Approval

Rohrkupplung / Pipe coupling  
"Fig. 1G"

Verwendung  
Use

in ortsfesten Wasserlöschanlagen  
in stationary water extinguishing systems

Anerkennungsgrundlagen  
Basis of the Approval

VdS 2344:2014-07  
VdS 2100-06:2004-01

Köln, den 14.07.2017

Dr. Reinermann

Geschäftsführer  
Managing Director

i. V. Hesels

Leiter der Zertifizierungsstelle  
Head of Certification Body

## Pipe Fittings

These fittings are suitable for interconnecting piping, valves and other components in both wet and dry automatic sprinkler systems. Installation should be according to applicable sprinkler system fabrication rules. These rules limit the minimum size of sprinkler piping to 1 in., nominal. FM Approved pipe fittings of smaller sizes are intended for use as valve trim, gauge connections, and for other peripheral service. The water flow path of the sprinkler system cannot be designed using smaller sizes than 1 in., nominal. Unless otherwise noted in the listing, these fittings have 175 psi (1205 kPa) rated working pressure.

Threaded connections on fittings can be made to FM Approved threadable thinwall pipe or to Schedule 40 pipe. Refer to the "Steel Pipe" listings for a summary of the various types of FM Approved steel pipe suitable for threading or grooving."

The fittings manufacturer's installation instructions must be observed in all cases. When connections are made to FM Approved pipe, the pipe manufacturer's installation instructions must also be followed.

Unless otherwise stated below, the maximum ambient temperature to which these fittings should be subjected is 225°F (107°C).

## Pipe Fittings

### Pipe Fittings

<i>Product Designation</i>	<i>Fitting Description</i>	<i>End Connection</i>	<i>Nominal Pipe Size, in.</i>	<i>Max Working Pressure, psi (kPa)</i>	<i>Remarks</i>
1#	90° Bend	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
1A	90° Bend Short	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 4	500 (3445)	a
2#	90° Bend	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
2A	90° Bend Short	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
3#	90° Bend	Male BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
40	45° Bend	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP X Female BSP	6	300 (2070)	a
41	45° Bend	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
85	Crossover	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
			1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	500 (3450)	a

90	90° Elbow	Grooved	76, 139.7, 165 mm	500 (3445)	a	
			1 76, 133 mm	500 (3445)	b	
			267.4, 318.5 mm	300 (2070)	b	
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a	
			5, 6	300 (2070)	a	
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a	
5, 6	300 (2070)		a			
90R	90° Reducing Elbow	NPT	1/2×1/4, 3/8 3/4 x 1/4, 3/8, 1/2 1 x 1/4, 3/8, 1/2, 3/4 1-1/4 x 3/8, 1/2, 3/4, 1 1-1/2 x 1/2, 3/4, 1, 1-1/4 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2 3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a	
			BSP	1/2×1/4, 3/8, 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×3/8, 1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 4×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
				6×4	300 (2070)	a
		Grooved	6 x 4 88.9 x 76.1 mm 114.3 x 76.1 mm 165.1 x 114.3 mm	500 (3445)	b	
			2, 2-1/2, 3, 4, 6, 8 76, 139.7, 165 mm	300 (2070)	a	

90S	90° Short Radius Elbow	Grooved	108, 159, 216.3 mm	300 (2070)	b
			114, 165 mm	365 (2510)	b
92	90° Street Elbow	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
92R	90° Reducing Street Elbow	BSP	3/4×1/2 1×3/4	500 (3445)	a
95	Union Elbow, Flat Seat without gasket	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
96	Union Elbow, Conical Joint Iron to Iron	Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
97	Union Elbow, Flat Seat without gasket	Male BSP X Female BSP	1/1/2002	500 (3445)	a
98	Union Elbow, Conical Joint Iron to Iron	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
105	11.25° Elbow	Grooved	1-1/4, 1-1/2, 2, 3, 4, 6 76.1, 108, 139.7, 159, 165.1 mm	500 (3445)	b
		Grooved	8	300 (2070)	b
110	22.5° Elbow	Grooved	1-1/4, 1-1/2, 2, 3, 4, 6 73, 76.1, 108, 139.7, 159, 165.1 mm	500 (3445)	b
		Grooved	8	300 (2070)	b

120	45° Elbow	Grooved	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 76.1, 165 mm	500 (3450)	a
			1 108, 139.7, 159 mm	500 (3445)	b
			216.3, 267.4, 318.5 mm	300 (2070)	b
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
		121	45° Street Elbow	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4
BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4			500 (3445)	a
130	Equal Tee	Grooved	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 76.1, 165 mm	500 (3450)	a
			1 76, 133, 139.7 mm	500 (3445)	b
			267.4 mm	300 (2070)	b
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
					2×1-1/2 3×1, 1-1/2, 2, 2-1/2 4×1, 2, 2-1/2, 3 5×2, 3, 4 6×2, 2-1/2, 3, 4, 5 8×2, 3, 4, 5, 6

	Reducing Tee	Grooved	2 x 1 2-1/2 x 1-1/2, 2 3 x 1-1/4 4 x 1-1/2 60 x 48 mm 76.1 x 42.4, 48.3, 60.3 mm 88.9 x 48, 60, 73, 76.1 mm 108 x 60.3, 73, 88.9 mm 114.3 x 34, 60, 73, 76.1, 88.9 mm 133 x 60.3, 76.1, 108, 114.3 mm 139.7 x 48.3, 60.3, 76.1, 88.9, 114.3 mm 141 x 114.3 mm 159 x 60.3, 76.1, 88.9, 108, 114.3, 133 mm 168 x 60, 73, 89, 114, 141 mm	500 (3445)	b
			10 x 6, 8 12 x 8, 10 165.1 x 60.3, 76.1, 88.9, 114.3, 133, 139.7, 159 mm 168.3 x 76.1, 139.7 mm 216.3 x 165.1 mm 219.1 x 60, 76.1, 89, 108, 114.3, 133, 139.7, 141.3, 159, 165.1, 168 mm 273 x 165.1 mm 323.9 x 165.1 mm	300 (2070)	b
			1/2x1/2x1/4, 3/8 1/2x1/4x1/2 1/2x3/8x1/2 3/4x3/4x1/4, 3/8, 1/2 3/4x1/2x1/2, 3/4 1x1x1/4, 3/8, 1/2, 3/4 1x1/2x1/2, 3/4, 1 1x3/4x1/2, 3/4, 1 1-1/4x1/2x1/2, 3/4, 1, 1-1/4 1-1/4x3/4x3/4, 1, 1-1/4 1-1/4x1x1/2, 3/4, 1, 1-1/4, 1-1/2 1-1/4x1-1/4x3/8, 1/2, 3/4, 1 1-1/2x1/2x3/4, 1-1/2 1-1/2x3/4x1/2, 3/4, 1, 1-1/4, 1-1/2 1-1/2x1x1/2, 3/4, 1, 1-1/4, 1-1/2 1-1/2x1-1/4x1/2		

130R	Reducing Tee	NPT	<p>3/4, 1, 1-1/4, 1-1/2, 2 1-1/2×1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2×2 2×3/4×2 2×1×1, 1-1/2, 2 2×1-1/4×1, 1-1/4, 1-1/2, 2 2×1-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 2×2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1-1/2×2, 2-1/2 2-1/2×2×2, 2-1/2 2-1/2×2-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 3×2×2, 3 3×3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 4×4×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3</p>	500 (3445)	a
	Reducing Tee	BSP	<p>1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×3/8, 1/2, 3/4, 1 1-1/2×3/8, 1/2, 3/4, 1, 1-1/4 2×3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×3/4, 1/2, 1, 1-1/4, 1-1/2, 2 3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 4×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 1/2×1/2×3/4, 1 3/4×3/4×1, 1-1/4 1×1×1-1/4, 1-1/2, 2, 2-1/2 1-1/4×1-1/4×1-1/2, 2 1-1/2×1-1/2×2, 2-1/2 2×2×2-1/2 2-1/2×2-1/2×3, 4 3/4, 1 ×1/2×1/2 1, 1-1/4, 1-1/2 ×3/4×3/4 1-1/4×1/2×1/2 1-1/4, 1-1/2, 2 ×1×1 1-1/2, 2 ×1-1/4×1-1/4 2×1-1/2×1-1/2 2-1/2, 3 ×2×2 3/4×1/2×3/4 1×1/2×1, 1×3/4×1,</p>	500 (3445)	a

			<p>1×1/4×1                  1-1/4×1/2×1-1/4,                  1-1/4×3/4×1-1/4,                  1-1/4×1×1-1/4                  1-1/2×1/2×1-1/2,                  1-1/2×3/4×1-1/2,                  1-1/2×1×1-1/2,                  1-1/2×1-1/4×1-1/2                  2×1/2×2, 2×3/4×2,                  2×1×2,                  2×1-1/4×2,                  2×1-1/2×2                  2-1/2×1-1/2×2-1/2,                  2-1/2×2×2-1/2                  3/4×1/2×1,                  1×1/2×3/4,                  1×3/4×1/2                  1-1/4×1/2×3/4, 1                  1-1/4×3/4×1/2, 1                  1-1/4×1×1/2, 3/4                  1-1/2×3/4×1, 1-1/4                  1-1/2×1×1/2, 1-1/4                  1-1/2×1-1/4×1/2,                  3/4, 2                  2×1×1-1/2                  2×1-1/4×1, 1-1/2                  2×1-1/2×3/4, 1,                  1-1/4                  2-1/2×2×1/2, 1,                  1-1/4</p>		
			6×2, 3, 4	300 (2070)	a
	Bullhead Tee	NPT	<p>3/8×3/8×1/2                  1/2×1/2×3/4, 1                  3/4×3/4×1                  1×1×1-1/4, 1-1/2,                  2                  1-1/4×1-1/4×1-1/2,                  2                  1-1/2×1-1/2×2                  2×2×2-1/2</p>	500 (3445)	a
130S	Short Radius Tee	Grooved	2, 2-1/2, 3, 4, 6, 8 76, 139.7, 165 mm	300 (2070)	a
			108, 159, 216.3 mm	300 (2070)	b
			114, 165 mm	365 (2510)	b
131	Equal Tee	Grooved	3, 4, 6	300 (2070)	b
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
			<p>2 x 1, 1-1/2                  2-1/2 x 1, 1-1/4,                  3 x 1, 1-1/4,                  1-1/2, 2                  4 x 1, 1-1/4,                  1-1/2, 2, 3                  6 x 2, 3                  8 x 2, 3, 4                  76.1 x 33.7, 42.4,</p>		



131R	Reducing Tee	Grooved	48.3, 60.3 mm 88.9 x 76.1 mm 108 x 60.3, 76.1, 88.9 mm 114.3 x 76.1 mm 133 x 60.3, 76.1, 88.9 mm 139.7 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 mm 159 x 60.3, 76.1, 88.9 mm 165.1 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9, 114.3 mm 168.3 x 76.1 mm 219.1 x 76.1 mm	300 (2070)	b
134	Service Tee	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
134R	Service Tee Reducing	BSP	2x1-1/2 2-1/2x2 3x2-1/2	500 (3445)	a
165	Lateral Y Branch	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
180	Equal Cross	Grooved	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 76.1, 165 mm	500 (3450)	a
			60, 73, 76, 89, 108, 114, 139.7, 141, 159, 165, 168 mm	500 (3450)	b
			219 mm	300 (2070)	b
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		Grooved	3 x 2 4 x 2, 3 8 x 2, 4 139.7 x 114.3 mm 159 x 108 mm 165.1 x 60.3, 76.1, 88.9, 114.3 mm	500 (3450)	b
			219.1 x 139.7, 159, 165.1 mm	300 (2070)	b

180R	Reducing Cross	NPT	3/4×1/2 1×3/4 1-1/4×3/4, 1 1-1/2×3/4, 1/1-1/4 2×3/4, 1/1-1/4, 1-1/2 2-1/2×1, 1-1/4, 1-1/2, 2 3×1, 1-1/4, 1-1/2, 2, 2-1/2 4×2-1/2, 3	500 (3445)	a
		BSP	3/4×1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×3/4, 1, 1-1/4, 1-1/2 2-1/2×3/4, 1, 1-1/4, 1-1/2, 2 3×3/4, 1, 1-1/4, 1-1/2, 2 4×1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
181R	Reducing Cross	Grooved	4 x 1, 1-1/4, 1-1/2, 2 165.1 x 60.3 mm	300 (2070)	b
220	Coupling	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
230	Eccentric Reducer	Grooved	4 x 2, 3 6 x 3, 4 8 x 4 88.9 x 60.3 mm 108 x 76.1, 88.9 mm 114.3 x 76.1 mm 139.7 x 114.3 mm 159 x 108, 114.3 mm 165.1 x 88.9, 114.3, 139.7 mm 168.3 x 139.7 mm	300 (2070)	b
			219 x 168 mm 273 x 219 mm	365 (2510)	b
230N	Eccentric Reducer	Grooved x Female NPT	108 x 76.1 mm 114.3 x 76.1 mm 139.7 x 88.9 mm 165.1 x 88.9 mm	300 (2070)	b
		NPT	1/2×3/8 3/4×3/8, 1/2 1×3/8, 1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1,	500 (3445)	a

240	Reducing Socket		1-1/4, 1-1/2 2-1/2×1-1/2, 2 3×1-1/2, 2, 2-1/2 4×2, 3		
		BSP	1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×1/4, 3/8, 1/2, 3/4, 1 1-1/2×1/4, 3/8, 1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500 (3445)	a
240	Concentric Reducer	Grooved	2×3/4, 1, 1-1/4, 1-1/2 2-1/2×1, 1-1/4, 1-1/2, 2 3×3/4, 1, 1-1/2, 2, 2-1/2 4×1, 1-1/2, 2, 2-1/2, 3 5×3, 4 6×1, 2, 2-1/2, 3, 4, 5 8×2-1/2, 3, 4, 5, 6	500 (3450)	a
			Grooved	1-1/4 x 1 1-1/2 x 1, 1-1/4 4 x 1-1/4 5 x 2-1/2 76 x 42, 48, 60 mm 89 x 42, 76 mm 108 x 60.3, 73, 76 mm 114.3 x 76.1 mm 133 x 108, 114.3 mm 139.7 x 60.3, 76.1, 88.9, 114.3 mm 141 x 89, 114 mm 159 x 60.3, 76.1, 88.9, 108, 114.3, 133 mm 165.1 x 60.3, 76.1, 88.9, 114.3, 139.7 mm 168.3 x 76.1, 139.7 mm	500 (3450)
		216.3 x 114.3, 165.1 mm 219.1 x 108, 139.7, 159, 165.1 mm 273 x 159, 165.1, 168.3, 219.1 mm 322.9 x 219.1, 273 mm		300 (2070)	b

240N	Concentric Reducer	Grooved × Female NPT	2×3/4, 1, 1-1/4, 1-1/2 2-1/2×1, 1-1/4, 1-1/2, 2 3×3/4, 1, 1-1/2, 2, 2-1/2 4×1, 1-1/2, 2, 2-1/2, 3 5×3, 4 6×2, 2-1/2, 3, 4, 5 8×2-1/2, 3, 4, 5, 6	500 (3450)	a
			4 x 1/2, 3/4, 1-1/4 8 x 1-1/2, 2 76 x 21, 27, 34, 42, 48, 60 mm 89 x 21, 76 mm 108 x 34, 42, 48, 60, 76, 89 mm 114 x 76 mm 133 x 48, 76 mm 139.7 x 27, 34, 42, 48, 60, 76, 89, 114 mm 141.3 x 89, 114 mm 159 x 27, 34, 42, 48, 60, 89, 114 mm 165 x 21, 27, 34, 42, 48, 60, 76, 89, 114 mm 219 x 76 mm	500 (3450)	b
240W	Concentric Reducer	Grooved × NPT	2×3/4, 1, 1-1/4, 1-1/2 2-1/2×1, 1-1/4, 1-1/2, 2 3×3/4, 1, 1-1/2, 2, 2-1/2 4×1, 1-1/2, 2, 2-1/2, 3 5×3, 4 6×2, 2-1/2, 3, 4, 5 8×2-1/2, 3, 4, 5, 6	500 (3450)	a
			76 x 60 mm	500 (3450)	b
		NPT	1/2×1/4, 3/8 3/4×3/8, 1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×3/8, 1/2, 3/4, 1, 1-1/4 2×3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 3×1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2 3-1/2×2-1/2, 3 4×3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2	500 (3445)	a

241	Bushing		5×2, 3, 4 6×2, 2-1/2, 3, 3-1/2, 4, 5	300 (2070)	a
		BSP	1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/4, 3/8, 1/2, 3/4 1-1/4×1/4, 3/8, 1/2, 3/4, 1 1-1/2×1/4, 3/8, 1/2, 3/4, 1, 1-1/4 2×1/4, 3/8, 1, 1-1/4, 1-1/2 2-1/2×1/2, 3/4, 1-1/2, 2 3×2, 2-1/2 3-1/2×3 4×3/4, 1, 1-1/4, 1-1/2, 3	500 (3445)	a
			5×3, 4 6×2, 2-1/2, 5	300 (2070)	a
241D	Bushing	BSP	2×1/2, 3/4 2-1/2×1, 1-1/4 3×1/2, 3/4, 1, 1-1/4, 1-1/2 4×2, 2-1/2	500 (3445)	a
			6×3, 4	300 (2070)	a
245	Hex Nipple Reducing	BSP	1/2×1/4, 3/8 3/4×1/4, 3/8, 1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1, 1-1/4, 1-1/2 3×1-1/2, 2, 2-1/2 4×2, 4×2-1/2, 4×3	500 (3445)	a
246	Extension Reducing	Male BSP X Female BSP	1/2×1/4, 3/8 3/4×3/8, 1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×3/4, 1, 1-1/4 2×1, 1-1/4, 1-1/2	500 (3445)	a
270	Socket	BSP Parallel Threads	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
271	Socket	BSP Right and Left Threads	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500 (3445)	a

280	Hex Nipple	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
291	Plug, Sq. Hd.	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
291-4	Plug, Cross slotted	NPT	4	500 (3445)	a
			5, 6	300 (2070)	a
291N	Plug, Sq. Socket	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
291S	Plug, Solid Sq.	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
300	End Cap	Grooved	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 76.1, 165 mm	500 (3450)	a
			1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 76.1, 89, 114, 140, 165 mm	500 (3450)	b
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			5, 6	300 (2070)	a
300PX	End Cap	Grooved × BSP	89 x 48, 60 mm 114 x 48, 60 mm 140 x 48, 60 mm 165 x 48 mm 168 x 48, 60 mm	500 (3445)	b
			219 x 48, 60 mm	300 (2070)	b
310	Locknut	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a

312	Backnut	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 4	500 (3445)	a
321	Flange Adapter	Flanged x NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
321-4	Flange Adapter	Flanged x BSP	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
321-6	Flange Adapter	Flanged x BSP	1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
			6	300 (2070)	a
321G	Flange Adapter	Flanged x Grooved	2, 2-1/2, 3, 4, 5, 6, 8 76.1, 165 mm	500 (3450)	a
			1, 1 1/4, 1 1/2, 10, 12 108, 133, 139.7, 159 mm	300 (2070)	a
			60, 73, 76.1, 89, 114 mm	365 (2510)	b
			139.7, 141.3, 165, 168, 219, 273, 324 mm	225 (1550)	b
321H	Flange Adapter	Flanged x BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
321N	Flange Adapter	Flanged x BSP	2	500 (3450)	a
321P	Flange Adapter	Flanged x BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
			5, 6	300 (2070)	a
321PW	Flange Adapter	Flanged x BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
			5, 6	300 (2070)	a
321TD	Flange Adapter	Flanged x BSP	1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
			6	300 (2070)	a
321W	Flange Adapter	Flanged x BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	a
330	Union Flat Seat without gasket	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a

331	Union Flat Seat without gasket	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
340	Union Conical Joint Iron to Iron	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
340F	Union Nut	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
341	Union Conical Joint Iron to Iron	Male BSP X Female BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
342	Union Conical Joint Brass to Iron	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
526	Extension	BSP	1/2	500 (3445)	a
529	Extension	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3445)	a
529A	Extension Long	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
529X	Extension Short	BSP	1/2	500 (3445)	a
1090	90° Elbow Plain	BSP	1/2, 3/4, 1, 1-1/4, 2	500 (3445)	a
1130	Equal Tee Plain	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
1220	Socket Plain	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	a
1221	Side Outlet Elbow	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3445)	a
		BSP	1/2, 3/4, 1, 1-1/4, 2	500 (3445)	a
1223	Side Outlet Tee	BSP	1/2, 3/4, 1	500 (3445)	a
Steel Merchant Socket	Socket	BSP	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	d
			4, 5, 6	300 (2070)	d
		NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	500 (3445)	d
			4, 5, 6	300 (2070)	d



**Remarks:**

- a. Malleable Iron Fittings
- b. Ductile Iron Fittings
- c. Cast Iron Fittings
- d. Steel Fittings

Product Designation	Fitting Description	End Connection	Nominal Pipe Size, in.	Max Working Pressure, psi (kPa)	Remarks
35C	Cap	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500 (3450)	b
35CP	Straight Coupling	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500 (3450)	b
35E	90° Elbow	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	b
35F	45° Elbow	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	500 (3450)	b
35HB	Bushings	NPT	1×1/2, 3/4 1-1/4×3/4, 1 1-1/2×1, 1-1/4 2×1, 1-1/4, 1-1/2	500 (3450)	b
35RC	Concentric Reducer	NPT	1×1/2, 3/4 1-1/4×3/4, 1 1-1/2×1, 1-1/4 2×1, 1-1/4, 1-1/2	500 (3450)	b
35RE	90° Reducing Elbow	NPT	3/4×1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×1-1/2, 2 3×3/4	500 (3450)	b
			3/4×3/4×1/2, 1 3/4×1/2×3/4, 1/2 1×1×1/2, 3/4, 1-1/4, 1-1/2 1×3/4×3/4, 1 1×1/2×1 1-1/4×1-1/4×1/2, 3/4, 1, 1-1/2, 2 1-1/4×1×1/2, 3/4, 1, 1-1/4, 1-1/2 1-1/4×3/4×1-1/4 1-1/4×1/2×1-1/4 1-1/2×1-1/2×1/2, 3/4, 1, 1, 1-1/4, 2 1-1/2×1-1/4×1/2, 3/4, 1, 1-1/4,		

35RT	Reducing Tee	NPT	1-1/2, 2 1-1/2×1×1/2, 3/4, 1, 1-1/4, 1-1/2 1-1/2×3/4×1-1/4, 1-1/2 1-1/2×1/2×1-1/4, 1-1/2 2×2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2-1/2 2×1-1/2×1/2, 3/4, 1, 1-1/4, 1-1/2, 2 2×1-1/4×2 2×1×2 2-1/2×2-1/2×3/4, 1, 1-1/4, 1-1/2, 2, 3	500 (3450)	b
35RX	Reducing Cross	NPT	1-1/4×1 1-1/2×1 2×1	500 (3450)	b
35SP	Square Head Pipe Plug	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500 (3450)	b
35T	Equal Tee	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	500 (3450)	b
35U	Union	NPT	1, 1-1/4, 1-1/2, 2	500 (3450)	b
35X	Cross	NPT	1, 1-1/4, 1-1/2, 2	500 (3450)	b
37E	90° Elbow	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300 (2070)	c
37F	45° Elbow	NPT	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300 (2070)	c
37RC	Concentric Reducer	NPT	1×1/2, 3/4 1-1/4×1 2×3/4, 1	300 (2070)	c
37RE	90° Reducing Elbow	NPT	3/4×1/2 1×1/2, 3/4 1-1/4×1/2, 3/4, 1 1-1/2×1/2, 3/4, 1, 1-1/4 2×1/2, 3/4, 1, 1-1/4, 1-1/2 2-1/2×3/4, 1, 1-1/4, 1-1/2, 2 3×2	300 (2070)	c

37RT	Reducing Tee	NPT	<p>3/4x3/4x1                      1x1/2x1/2, 3/4, 1                      1x3/4x1/2, 3/4, 1                      1x1x1/2, 3/4,                      1-1/4, 1-1/2                      1x1-1/4x1                      1-1/4x1-1/4x1/2,                      3/4, 1, 1-1/2, 2                      1-1/4x1x1/2,                      3/4, 1, 1-1/4,                      1-1/2,                      1-1/4x3/4x1-1/4                      1-1/4x1/2x1-1/4                      1-1/2x1-1/2x1/2,                      3/4, 1, 1, 1-1/4, 2                      1-1/2x1-1/4x1/2,                      3/4, 1, 1-1/4,                      1-1/2, 2                      1-1/2x1x1/2,                      3/4, 1, 1-1/4,                      1-1/2, 2                      1-1/2x3/4x1-1/4,                      1-1/2                      1-1/2x1/2x1-1/4,                      1-1/2                      2x2x1/2, 3/4, 1,                      1-1/4, 1-1/2,                      2-1/2                      2x1-1/2x1/2,                      3/4, 1, 1-1/4,                      1-1/2, 2, 2-1/2                      2x1-1/4x1/2, 1,                      1-1/4, 1-1/2, 2                      2x1x3/4, 1,                      1-1/4, 1-1/2, 2                      2x1/2x2                      2x2x2-1/2                      2-1/2x2-1/2x1/2,                      3/4, 1, 1-1/4,                      1-1/2, 2                      2x1-1/4x2-1/2                      2x1x2-1/2                      2x3/4x2-1/2                      2-1/2x1/2x2,                      2-1/2                      3x3x1-1/4,                      1-1/2, 2</p>	300 (2070)	c
37T	Equal Tee	NPT	<p>1/2, 3/4, 1,                      1-1/4, 1-1/2, 2,                      2-1/2,                      3, 4</p>	300 (2070)	c

**Remarks:**

- a. Malleable Iron Fittings
- b. Ductile Iron Fittings
- c. Cast Iron Fittings

<b>Company Name:</b>	Rapidrop Global Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>

<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved



## VIZA.EX15952 Fittings, Grooved and Plain End

[Page Bottom](#)

### Fittings, Grooved and Plain End

[See General Information for Fittings, Grooved and Plain End](#)

**RAPIDROP GLOBAL LTD**

EX15952

RUTLAND BUSINESS PARK  
NEWARK RD  
PETERBOROUGH, PE1 5WA UNITED KINGDOM

The following fittings are intended for use with Listed Rapidrop Global (EX15953) rubber gasketed fittings.

**Grooved**

Model	Type	Size In.	Rated Pressure (psig)
90	90 Degree Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 5-1/2 OD, 6, 6-1/2 OD, 8	500
90	90 Degree Elbow	33.7mm, 76.1mm	500
90	90 Degree Elbow	133.0mm, 267.4mm, 318.5mm	300
90	90 Degree Elbow	10	300
90	90 Degree Elbow	12	225
90S	90 Degree Short Elbow	2, 2-1/2, 3 OD, 3, 4, 5-1/2 OD, 6, 6-1/2 OD, 8	300
90S	90 Degree Short Elbow	108.0mm	500
90S	90 Degree Short Elbow	159.0mm, 216.3mm	300
90S	90 Degree Short Elbow	114.3mm, 165.1mm	365
90S	90 Degree Short Elbow	159.0mm, 216.3mm	300
90R	90 Degree Reducing Elbow	88.9 x 76.1mm;	300
		114.3 x 76.1mm, 88.9mm;	
		165.1 x 114.3mm;	
		168.3 x 114.3mm	
105	11.25 Degree Elbow	42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	500
105	11.25 Degree Elbow	108.0mm, 114.3mm, 139.7mm, 159.0mm, 165.1mm, 168.3mm, 219.1mm	300
110	22.5 Degree Elbow	42.4mm, 48.3mm, 60.3mm, 73.0mm, 76.1mm, 88.9mm	500
110	22.5 Degree Elbow	108.0mm, 114.3mm, 139.7mm, 159.0mm, 165.1mm, 168.3mm, 219.1mm	300
120	45 Degree Elbow	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
120	45 Degree Elbow	33.7mm	500
120	45 Degree Elbow	108.0mm, 139.7mm, 159.0mm, 216.3mm, 267.4mm, 318.5mm	300
130	Tee	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
130	Reducing Tee	2 x 1-1/2;	500
		3 x 1, 1-1/2, 2, 2-1/2;	
		4 x 1, 2, 2-1/2, 3;	
		5 x 2, 3, 4;	
		6 x 2, 2-1/2, 3, 4, 5;	
		8 x 2, 3, 4, 5, 6	
130	Reducing Tee	60.3 x 33.7mm, 48.3mm	500

		73.0 x 48.3mm, 60.3mm;	
		76.1 x 42.4mm, 48.3mm, 60.3mm;	
		88.9 x 42.4mm, 48.3mm, 60.3mm, 73.0mm	
130	Reducing Tee	114.3 x 33.7mm, 60.3mm, 73.0mm, 88.9mm;	365
		141.3 x 88.9mm, 114.3mm;	
		168.3 x 60.3mm, 73.0mm, 88.9mm, 114.3mm, 141.3mm	
130	Reducing Tee	88.9 x 76.1mm;	300
		108.0 x 60.3mm, 73.0mm, 88.9mm;	
		114.3 x 48.3mm, 76.1mm;	
		133.0 x 60.3mm, 76.1mm, 108.0mm, 114.3mm;	
		139.7 x 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		159.0 x 60.3mm, 76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm;	
		165.1 x 60.3mm, 76.1mm, 88.9mm, 114.3mm, 133.0mm, 139.7mm, 159.0mm;	
		168.3 x 76.1mm, 139.7mm;	
		216.3 x 165.1mm;	
		219.1 x 60.3mm, 76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm, 139.7mm, 141.3mm, 159.0mm, 165.1mm; 168.3mm	
		273.0 x 165.1mm, 168.3mm, 219.1mm;	
		323.9 x 165.1mm, 219.1mm, 273.0mm	
130S	Short Tee	2, 2-1/2, 3 OD, 3, 4, 5-1/2 OD, 6, 6-1/2 OD, 8	300
130S	Short Tee	108.0mm	500
130S	Short Tee	114.3mm, 165.1mm	365
130S	Short Tee	159.0mm, 216.3mm	300
131	Tee	88.9mm, 114.3mm, 168.3mm	300
131	Reducing Tee	60.3 x 33.7mm, 48.3mm;	500
		73.0 x 33.7mm, 42.4mm;	
		76.1 x 33.7mm, 42.4mm, 48.3mm, 60.3mm;	
		88.9 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm	
131	Reducing Tee	108.0 x 60.3mm, 76.1mm, 88.9mm;	300
		114.3 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
		133.0 x 60.3mm, 76.1mm, 88.9mm;	
		139.7 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
		159.0 x 60.3mm, 76.1mm, 88.9mm;	
		165.1 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		168.3 x 60.3mm, 76.1mm, 88.9mm	
180	Cross	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 6, 6-1/2 OD, 8, 10, 12	500
180	Cross	60.3mm, 73.0mm, 76.1mm, 88.9mm, 114.3mm, 141.3mm, 165.1mm	365
180	Cross	108.0mm, 139.7mm, 159.0mm, 168.3mm, 219.1mm	300
180	Reducing Cross	88.9 x 60.3mm	500
180	Reducing Cross	114.3 x 60.3mm, 88.9mm;	300
		139.7 x 114.3mm;	
		159.0 x 108.0mm;	
		165.1 x 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		219.1 x 60.3mm, 114.3mm, 139.7mm, 159.0mm, 165.1mm	
181	181 Cross	114.3 x 33.7mm, 42.4mm, 48.3mm, 60.3mm;	300

		165.1 x 60.3mm	
230	Grooved Eccentric Reducer	88.9 x 60.3mm;	500
		108.0 x 76.1mm, 88.9mm;	
		114.3 x 60.3mm, 88.9mm	
230	Grooved Eccentric Reducer	114.3 x 76.1mm;	300
		139.7 x 114.3mm;	
		159.0 x 108.0mm, 114.3mm;	
		165.1 x 88.9mm, 114.3mm, 139.7mm;	
		168.3 x 88.9mm, 114.3mm, 139.7mm;	
		219.1 x 114.3mm, 168.3mm;	
		273.1 x 219.1mm	
230N	Grooved Eccentric Reducer With Male Thread	108.0 x 76.1mm	500
230N	Grooved Eccentric Reducer With Male Thread	114.3 x 76.1mm;	300
		139.7 x 88.9mm;	
		165.1 x 88.9mm	
240	Grooved Concentric Reducer	2 x 3/4, 1, 1-1/4, 1-1/2;	500
		2-1/2 x 1, 1-1/4, 1-1/2, 2;	
		3 x 3/4, 1, 1-1/2, 2, 2-1/2;	
		4 x 1, 1-1/2, 2, 2-1/2, 3;	
		5 x 3, 4;	
		6 x 1, 2, 2-1/2, 3, 4, 5;	
		8 x 2-1/2, 3, 4, 5, 6	
240	Grooved Concentric Reducer	42.4 x 33.7mm;	500
		48.3 x 33.7mm, 42.4mm;	
		76.1 x 42.4mm, 48.3mm, 60.3mm;	
		88.9 x 76.1mm;	
		108.0 x 60.3mm, 73.0mm	
240	Grooved Concentric Reducer	88.9 x 42.4mm;	365
		133.0 x 108.0mm, 114.3mm;	
		139.7 x 60.3mm;	
		141.3 x 88.9mm, 114.3mm	
240	Grooved Concentric Reducer	108.0 x 76.1mm;	300
		114.3 x 42.4mm, 76.1mm;	
		139.7 x 76.1mm, 88.9mm, 114.3mm;	
		141.3 x 73.0mm;	
		159.0 x 60.3mm, 76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm;	
		165.1 x 60.3mm, 76.1mm, 88.9mm, 114.3mm, 139.7mm;	
		168.3 x 76.1mm, 139.7mm;	
		216.3 x 114.3mm, 165.1mm;	
		219.1 x 108.0mm, 139.7mm, 159.0mm, 165.1mm;	
		273.0 x 159.0mm, 165.1mm, 168.3mm, 219.1mm;	
		323.9 x 219.1mm, 273.0mm	

240N	Concentric Reducer - FNPT	2 x 3/4, 1, 1-1/4, 1-1/2;	500
		2-1/2 x 1, 1-1/4, 1-1/2, 2;	
		3 x 3/4, 1, 1-1/2, 2, 2-1/2;	
		4 x 1, 1-1/2, 2, 2-1/2, 3;	
		5 x 3, 4;	
		6 x 1, 2, 2-1/2, 3, 4, 5;	
		8 x 2-1/2, 3, 4, 5, 6	
240N	Concentric Reducer With Female Thread	76.1 x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm	500
240N	Concentric Reducer With Female Thread	88.9 x 21.3mm;	365
		133.0 x 48.3mm, 76.1mm;	
		139.7 x 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		141.3 x 88.9mm, 114.3mm	
240N	Concentric Reducer With Female Thread	88.9 x 42.4mm, 76.1mm;	300
		108.0 x 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1 mm, 88.9mm;	
		114.3 x 21.3 mm, 26.9mm, 42.4mm, 76.1 mm;	
		159.0 x 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 88.9mm, 114.3mm;	
		165.1 x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm, 114.3mm;	
		219.1 x 48.3mm, 60.3mm, 76.1mm	
240W	Concentric Reducer - MNPT	2 x 3/4, 1, 1-1/4, 1-1/2;	500
		2-1/2 x 1, 1-1/4, 1-1/2, 2;	
		3 x 3/4, 1, 1-1/2, 2, 2-1/2;	
		4 x 1, 1-1/2, 2, 2-1/2, 3;	
		5 x 3, 4;	
		6 x 1, 2, 2-1/2, 3, 4, 5;	
		8 x 2-1/2, 3, 4, 5, 6	
240W	Concentric Reducer - MNPT	76.1 x 60.3mm	500
300	Cap	1-1/4, 1-1/2, 2, 2-1/2, 3 OD, 3, 4, 5, 5-1/2 OD, 6, 6-1/2 OD, 8, 10, 12	500
300	Cap	33.7mm	500
300	Cap	108.0mm, 133.0mm, 139.7mm, 159.0mm, 216.3mm	300
300	Cap	76.1 x 48.3mm	500
300	Cap	88.9 x 60.3mm;	365
		114.3 x 60.3mm;	
		139.7 x 60.3mm;	
		165.1 x 60.3mm	
300	Cap	88.9 x 21.3mm, 33,7mm, 48.3mm;	300
		114.3 x 21.3mm, 33.7mm, 48.3mm;	
		165.1 x 21.3mm, 33.7mm;	
		168.3 x 48.3mm	
300PX	Cap	88.9 x 48.3mm, 60.3mm;	365
		114.3 x 48.3mm, 60.3mm;	
		139.7 x 48.3mm, 60.3mm;	



		165.1 x 48.3mm;	
		168.3 x 48.3mm, 60.3mm	
300PX	Cap	219.1 x 48.3mm, 60.3mm	300
321G	Flange Adapter	2, 2-1/2, 3 OD, 3, 4, 5, 6, 6-1/2 OD, 8	300
321G	Flange Adapter	10, 12	225
321G	Flange Adapter	33.7mm, 42.4mm, 48.3mm, 60.3mm, 73.0mm,	300
		76.1mm, 88.9mm, 108.0mm, 114.3mm, 133.0mm,	
		139.7mm, 141.3mm, 159.0mm, 165.1mm, 168.3mm	
321G	Flange Adapter	219.1mm, 273.1mm, 323.9mm	225
321GH	Flange Adapter	108.0mm, 159.0mm	300
321GL	Flange Adapter	219.1mm, 273.0mm	225

Trademark and/or Tradename:  , "Rapidrop®", 

Last Updated on 2011-05-20

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".