

Use: heating systems and refrigeration circuits

Features

- Flat expansion tank with a rectangular shape to optimize spaces in closed circuits
- Rubber diaphragm fixed membrane
- 100% Made in Italy
- Produced according to the standards established by PED 2014/68/UE and DIN EN 13831 regulations
- Quality certified and guaranteed by international regulations
- High level of customization
- Epoxy powder exterior painting to guarantee a high level of protection against oxidation and a fine aesthetic final quality
- Accurate quality controls during all manufacturing process phases



Code	Model	Capacity	Dimension	Height	Water entry connection	Standard pre-loading pressure	Maximum working pressure	Working temperature	External finishing colour
		Liters	I x L	H mm	G		Bar	°C	
9106	RP200 / 6	6	200 x 515	100	M 3/4" Gas	1,5	3,0	-10 + 90	Red
9108	RP200 / 8	8	200 x 515	113	M 3/4" Gas	1,5	3,0	-10 + 90	Red
9110	RP200 / 10	10	200 x 515	128	M 3/4" Gas	1,5	3,0	-10 + 90	Red
9112	RP200 / 12	12	200 x 515	146	M 3/4" Gas	1,5	3,0	-10 + 90	Red
9206	RP220x450 / 6	6	220 x 450	63	M 3/8" Gas	1,0	3,0	-10 + 90	Grey

9208	RP220x450 / 8	8	220 x 450	87	M 3/8" Gas	1,0	3,0	-10 + 90	Grey
9210	RP220x450 / 10	10	220 x 450	125	M 3/8" Gas	1,0	3,0	-10 + 90	Grey
9606	RP220x550 / 6	6	220 x 550	62	M 3/8" Gas	1,0	3,0	-10 + 90	Grey
9608	RP220x550 / 8	8	220 x 550	80	M 3/8" Gas	1,0	3,0	-10 + 90	Grey
9610	RP220x550 / 10	10	220 x 550	92	M 3/8" Gas	1,0	3,0	-10 + 90	Grey
9612	RP220x550 / 12	12	220 x 550	107	M 3/8" Gas	1,0	3,0	-10 + 90	Grey
9306	RP238 / 6	6	238 x 516	70	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9308	RP238 / 8	8	238 x 516	80	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9310	RP238 / 10	10	238 x 516	100	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9312	RP238 / 12	12	238 x 516	120	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9314	RP238 / 14	14	238 x 516	141	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9406	RP250 / 6	6	250 x 438	65	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9408	RP250 / 8 v.90°	8	250 x 438	86	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9410	RP250 / 10	10	250 x 438	105	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9412	RP250 / 12	12	250 x 438	115	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9414	RP250 / 14	14	250 x 438	134	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9508	RP440x350 / 8	8	350 x 440	73	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9510	RP440x350 / 10	10	350 x 440	88	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9512	RP440x350 / 12	12	350 x 440	98	M 3/8" Gas	1,5	3,0	-10 + 90	Red
9514	RP440x350 / 14	14	350 x 440	116	M 1/2" Gas	1,5	3,0	-10 + 90	Red
9518	RP440x350 CE / 18	18	350 x 440	152	M 3/4" Gas	1,5	3,0	-10 + 90	Red
9524	RP440x350 CE / 24	24	350 x 440	184	M 3/4" Gas	1,5	3,0	-10 + 90	Red