

Direct heating Wall convectors

CWM 2000

**NEW****CWM 500-3000 P**

APPLICATION: Compact, wall mounted convector as a standalone heater, as an efficient interim heater in spring/autumn, or for additional heat demand in the living space, bathroom or utility rooms. The timeless and very slimline design blends into any surroundings.

EQUIPMENT/CONVENIENCE: Electronically controlled convector with an easy to read display and simple programming for even, silent and accurate heating of the indoor air. The required room temperature can be adjusted on the programming unit from +5 to +30 °C in 0.5 °C increments. Programmable weekly timer with 2 preset and 1 individually programmable time programs. With adaptive control as a learning function for achieving the comfort temperature in timer mode at precisely the right time. Programmable comfort and setback temperatures. Selectable window open detection function to avoid wasted energy. Frost protection at 7 °C. Omnipolar ON/OFF switch. High grade stainless steel tubular heater with aluminium coated steel fins. Robust metal casing. Very user friendly due to top mounted user interface and large, easily legible display. Adjustable childproofing to prevent unintentional or unauthorised modifications to the programming unit.

INSTALLATION/SERVICE: Straightforward, stable wall mounting needs one person only: The wall mounting bracket is fitted to the wall separately from the appliance and can be readjusted later. All that remains is to hook the appliance into place. The appliance has a power cable with right angle plug. Maintenance-free.

SAFETY: Integral safety temperature limiter.

- › Compact metal casing in a slimline design
- › Electronic controller with LCD
- › Weekly timer with 3 time programs, self-learning function and window open detection
- › Safety through overheating protection
- › Splashproof to IP 24, safety category I
- › Omnipolar ON/OFF switch
- › Tubular stainless steel heater with steel fins
- › Power cable with safety plug

Programming unit



Part No.	Model	Connected load	Height	Width	Depth
200254	CWM 500 P	0,5 kW	450 mm	348 mm	100 mm
200255	CWM 750 P	0,75 kW	450 mm	426 mm	100 mm
200256	CWM 1000 P	1,0 kW	450 mm	426 mm	100 mm
200257	CWM 1500	1,5 kW	450 mm	582 mm	100 mm
200258	CWM 2000	2,0 kW	450 mm	738 mm	100 mm
200259	CWM 2500	2,5 kW	450 mm	894 mm	100 mm
200260	CWM 3000 P	3,0 kW	450 mm	1050 mm	100 mm

Depth including wall mounting bracket

Specification

Model	CWM 500 P	CWM 750 P	CWM 1000 P	CWM 1500	CWM 2000	CWM 2500	CWM 3000 P
Power supply	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V	1/N/PE ~ 230 V
Frequency	50/- Hz	50/- Hz	50/- Hz	50/- Hz	50/- Hz	50/- Hz	50/- Hz
Rated voltage	230 V	230 V	230 V	230 V	230 V	230 V	~230 V
Rated current	2,2 A	3,3 A	4,3 A	6,5 A	8,7 A	10,9 A	13,0 A
Setting range	5 - 30 °C	5 - 30 °C	5 - 30 °C	5 - 30 °C	5 - 30 °C	5 - 30 °C	5 - 30 °C
IP-Rating	IP24	IP24	IP24	IP24	IP24	IP24	IP24
Protection class	I	I	I	I	I	I	I
Weight	4 kg	4.6 kg	4.6 kg	6 kg	7.7 kg	9.2 kg	10.9 kg
Colour	alpine white	alpine white	alpine white	alpine white	alpine white	alpine white	alpine white