

Destinatar

Expeditor

Firma
Referinta
Adresa
Phone
Fax
E-mail

Cod articol : **Customer pos. no.:**

60231404

Articol:

EVOPLUS B 180/250.40 M

Date pompa

Presiune nominala: 1600 kPa
Temperatura min. fluid: -10 °C
Temperatura max. fluid: 110 °C
EEI: ≤ 0,20

Presiune minima la nivelul apei:

Temperatura: °C 90 100
Presiune minima la nivelul apei: m 20 25

Date de functionare cerute

Debit:
Înălțime de pompare:
Fluid pompat (%):
Temperatura fluid: 20 °C
Densitate: 998.3 kg/m³
Vascozitate cinematica: 1.005 mm²/s
Presiune de vapori: 2.34 kPa



Date disponibile:

Debit:
Înălțime de pompare:

Materiale

Corp pompa: Cast iron 250 UNI ISO 185 with Cataphoresis
Rotor: Tecnopolimer
Arbore motor: Otel inox
Inel de etansare: EPDM
Carcasa motorului: Die cast aluminium with Cataphoresis
Flansa de inchidere: Otel inox
Suport inel de echilibrare: Otel inox

Curve tolerance according to ISO 9906



Date motor

Marca: DAB
Max. Power input P1: 0.61 kW
Tensiune nominala: 1~ 220-240 V 50 Hz
Curent nominal: 2.9 A
Grad de protecție: IP 44

Dimensiuni de gabarit mm

A1	19	D1	110	H2	273		
A2	14	D2	100	L	250		
B	419	D3	84	L1	125		
B1	93	D4	42	L2	125		
B2	326	H	230				
D	150	H1	220				

Masa 20 kg

Racorduri pompa:

Partea cu aspiratia: DN 40 / PN6, PN10, PN16
Partea cu refularea: DN 40 / PN6, PN10, PN16


Destinatar

Expeditor

Firma
Referinta
Adresa
Phone
Fax
E-mail

EVOPLUS B 180/250.40 M

Curve tolerance according to ISO 9906




Destinatar

Expeditor

Firma
Referinta
Adresa
Phone
Fax
E-mail

EVOPLUS B 180/250.40 M



Dimensiuni in mm

Racorduri pompa:

1
2
3
4
5
6
7
8
9
10
11

A1
A2
B
B1
B2
D
D1
D2
D3
D4
H

19
14
419
93
326
150
110
100
84
42
230

H1
H2
L
L1
L2

220
273
250
125
125

Aspiratie
DN 40
PN6, PN10, PN16

Refulare
DN 40
PN6, PN10, PN16

MAIN_PROJECT_TITLE

BUSINESS_PROCESS_ID

OWNER_

ISSUE_DATE

11/24/2025