



245 Hexagon nipple, reducing, ISO/EN N8

- ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations.

EN	B/G	Dim. (1-2) [inch]	Code	a [mm]	s [mm]
ST -	B	1/4 - 1/8	770 245 115	35	17
ST -	G	1/4 - 1/8	770 245 215	35	17
ST -	B	3/8 - 1/8	770 245 116	34	19
ST -	G	3/8 - 1/8	770 245 216	34	19
ST •	B	3/8 - 1/4	770 245 117	38	19
ST •	G	3/8 - 1/4	770 245 217	38	19
•	B	1/2 - 1/4	770 245 118	44	27
•	G	1/2 - 1/4	770 245 218	44	27
•	B	1/2 - 3/8	770 245 119	44	22
•	G	1/2 - 3/8	770 245 219	44	22
-	B	3/4 - 1/4	770 245 120	43	30
-	G	3/4 - 1/4	770 245 220	43	30
•	B	3/4 - 3/8	770 245 121	47	30
•	G	3/4 - 3/8	770 245 221	47	30
•	B	3/4 - 1/2	770 245 122	47	31
•	G	3/4 - 1/2	770 245 222	47	31
•	B	1 - 1/2	770 245 123	53	36
•	G	1 - 1/2	770 245 223	53	36
•	B	1 - 3/4	770 245 124	53	36
•	G	1 - 3/4	770 245 224	53	36
•	B	1 1/4 - 1/2	770 245 125	57	46
•	G	1 1/4 - 1/2	770 245 225	57	46
•	B	1 1/4 - 3/4	770 245 126	57	46
•	G	1 1/4 - 3/4	770 245 226	57	46
•	B	1 1/4 - 1	770 245 127	57	46
•	G	1 1/4 - 1	770 245 227	57	46
•	B	1 1/2 - 3/4	770 245 128	59	50
•	G	1 1/2 - 3/4	770 245 228	59	50
•	B	1 1/2 - 1	770 245 129	59	50
•	G	1 1/2 - 1	770 245 229	59	50
•	B	1 1/2 - 1 1/4	770 245 130	59	50
•	G	1 1/2 - 1 1/4	770 245 230	59	50
•	B	2 - 1	770 245 131	68	65
•	G	2 - 1	770 245 231	68	65
•	B	2 - 1 1/4	770 245 132	68	65
•	G	2 - 1 1/4	770 245 232	68	65
•	B	2 - 1 1/2	770 245 133	68	65
•	G	2 - 1 1/2	770 245 233	68	65
-	B	2 1/2 - 1 1/2	770 245 134	75	80
-	G	2 1/2 - 1 1/2	770 245 234	75	80
•	B	2 1/2 - 2	770 245 135	75	80
•	G	2 1/2 - 2	770 245 235	75	80
•	B	3 - 2	770 245 136	83	95
•	G	3 - 2	770 245 236	83	95
•	B	3 - 2 1/2	770 245 137	83	95
•	G	3 - 2 1/2	770 245 237	83	95
-	B	4 - 3	770 245 138	96	120
-	G	4 - 3	770 245 238	96	120