

INSULATING WALLPAPER FOR INTERIOR WALLS, ALUMINIUM-LAMINATED, 4 MM**Product data:**

Article no:	9493
EAN code:	4007155159979
Format:	5 m x 0.5 m x ~ 4 mm (2.5 m ² /roll)
VPE:	11 rolls/carton

**Range of application and advantages:**

- with heat-reflecting aluminium surface
- Reflects 95 % of heat back into the room
- Reduces heat loss through the wall by up to 16 %*.
- Helps heat up rooms faster
- creates hand-warm walls
- Simple wall bonding with solvent-free polystyrene adhesive

*in relation to an uninsulated, 24 cm thick brick masonry wall

Technical data:

Material:	Polystyrene, EPS
Material thickness:	~ 4 mm
Building material class:	EN 13501-1 E (glued to plasterboard with polystyrene adhesive)
Thermal conductivity group:	WLG 040
Temperature resistance:	short term up to +75°C long-term up to +60°C

The aluminium-laminated insulation wallpaper is recyclable.

Processing:

The substrate must be clean, dry, firm, smooth and load-bearing. Cut the insulation material to length. Apply the recommended adhesive with a notched trowel to the entire back surface. Then glue the insulation material behind the radiator, butt to butt, and press on firmly with a rubber roller.

Adhesive consumption: up to 500 g/m²

Subject to technical changes. Due to the different processing and application conditions on site, this information only represents general notes from which no legal obligations can be derived.

Date: 03.12.2020