



ELGEF Plus Transition fitting PE/steel d20-400mm / SDR11

- 10 bar Gas / 16 bar Water
- Electrofusion weldable
- PE coated for corrosion resistance
- Steel pipe with weld-on end
- * Steel pipe galvanized

	d	d2	DN	PN	Code	Weight	Lmax	Q1	Q2
	(mm)	(inch)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)
*	20	¾	15	16	775 641 502	0.450	425	80	15
	25	¾	20	16	775 641 507	0.658	470	90	35
	32	1	25	16	775 641 510	0.988	470	96	35
	40	1 ¼	32	16	775 641 514	1.208	468	100	35
	50	1 ½	40	16	775 641 518	1.355	480	110	35
	63	2	50	16	775 641 524	2.011	480	110	35
	75	2 ½	65	16	775 641 632	2.983	540	127	35
	90	3	80	16	775 641 636	3.762	575	141	45
	110	3	100	16	775 641 640	4.381	585	145	45
	110	4	100	16	775 641 641	6.633	585	145	45
	125	4	100	16	775 641 645	6.833	585	148	45
	160	6	150	16	775 641 655	12.406	610	158	45
	180	6	150	16	775 641 659	11.935	665	225	45
	200	8	200	16	775 642 664	19.647	620	155	45
	225	8	200	16	775 642 669	20.154	600	145	45
	250	8	250	16	775 642 665	21.354	660	217	45
	250	10	250	16	775 642 666	30.000	690	186	45
	280	10	250	16	775 642 673	31.000	673	186	45
	315	12	300	16	775 642 672	35.000	730	215	45
	355	12	350	16	775 642 675	49.000	741	248	45
	400	16	400	16	775 642 678	94.000	770	190	45

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>