


Tranzitie mufa electrofuziune PE/alama (CW617N) Filet exterior



- **PE 100 SDR 11** (ISO S5)
- 10 bar Gaz / 16 bar Apa
- Cu sistem integrat de fixare
- Conectori de 4 mm
- Martori de sudura cu deplasare limitata
- Supplied as a kit with ELGEF Plus coupler or *ELGEF Plus reducer



d	Thread Type	Inch	DN	PN	Cod	Greutate
(mm)		(inch)	(mm)	(bar)		(kg)
20	R	½	15	16	720 920 756	0,187
20	R	1	15	16	720 920 754	0,344
25	R	¾	20	16	720 920 757	0,254
25	R	1	20	16	720 920 763	0,340
32	R	½	25	16	720 920 764	0,213
32	R	¾	25	16	720 920 765	0,268
32	R	1	25	16	720 920 758	0,340
32	R	1 ¼	25	16	720 920 766	0,489
32	R	1 ½	25	16	720 920 767	0,635
32	R	2	25	16	720 920 768	1,000
40	R	1	32	16	720 920 771	0,364
40	R	1 ¼	32	16	720 920 759	0,514
40	R	1 ½	32	16	720 920 772	0,645
40	R	2	32	16	720 920 773	0,961
50	R	1	40	16	720 920 776	0,367
50	R	1 ¼	40	16	720 920 777	0,554
50	R	1 ½	40	16	720 920 760	0,652
50	R	2	40	16	720 920 778	0,971
63	R	1	50	16	720 920 781	0,441
63	R	1 ¼	50	16	720 920 782	0,600
63	R	1 ½	50	16	720 920 783	0,712
63	R	2	50	16	720 920 761	0,943

d	Do	Lmax	P1	SLW	SDR teava
(mm)	(mm)	(mm)	(mm)	(mm)	
20	31	110	34	30	9-11
20	44	124	34	40	9-11
25	36	111	34	35	9-11
25	44	124	34	40	9-11
32	44	121	34	30	9-11
32	44	122	34	35	9-11
32	44	117	34	40	9-11
32	54	135	34	50	9-11
32	60	143	34	60	9-11
32	81	157	34	70	9-11
40	54	133	39	40	9-11
40	54	127	39	50	9-11
40	66	143	39	60	9-11
40	81	157	39	70	9-11
50	66	141	43	40	9-11
50	66	143	43	50	9-11
50	66	135	43	60	9-11
50	81	157	43	70	9-11
63	81	151	46	40	9-11
63	81	153	46	40	9-11
63	81	153	46	60	9-17.6
63	81	147	46	70	9-17.6

Fisa tehnica

valabil de la: 25.01.2025



Datele tehnice nu sunt obligatorii. Acestea nu constituie garantia caracteristicilor, a proprietatilor sau a durabilitatii. Acestea sunt supuse modificarii. Se aplica Condiitiile noastre Generale de Vanzare.

Georg Fischer GmbH Albershausen SA Sucursala Bucuresti, Tel. +40 31 104 0492, Internet: www.gfps.com/ro