



## 245 Hexagon nipple, reducing, ISO/EN N8

- ST ... these types of fittings are made from steel (galvanised finish = electroplated) and not suitable for drinking water installations.

| EN   | Dim. (1-2)<br>(inch) | Black<br>Code | Galvanised<br>Code | SP | GP  | a<br>(mm) | s<br>(mm) |
|------|----------------------|---------------|--------------------|----|-----|-----------|-----------|
| ST - | 1/4 - 1/8            | 770 245 115   | 770 245 215        | 10 | 100 | 35        | 17        |
| ST - | 3/8 - 1/8            | 770 245 116   | 770 245 216        | 10 | 100 | 34        | 19        |
| ST • | 3/8 - 1/4            | 770 245 117   | 770 245 217        | 10 | 100 | 38        | 19        |
| •    | 1/2 - 1/4            | 770 245 118   | 770 245 218        | 10 | 100 | 44        | 27        |
| •    | 1/2 - 3/8            | 770 245 119   | 770 245 219        | 10 | 100 | 44        | 22        |
| -    | 3/4 - 1/4            | 770 245 120   | 770 245 220        | 10 | 80  | 43        | 30        |
| •    | 3/4 - 3/8            | 770 245 121   | 770 245 221        | 10 | 50  | 47        | 30        |
| •    | 3/4 - 1/2            | 770 245 122   | 770 245 222        | 10 | 120 | 47        | 31        |
| •    | 1 - 1/2              | 770 245 123   | 770 245 223        | 10 | 80  | 53        | 36        |
| •    | 1 - 3/4              | 770 245 124   | 770 245 224        | 10 | 80  | 53        | 36        |
| •    | 1 1/4 - 1/2          | 770 245 125   | 770 245 225        | 0  | 25  | 57        | 46        |
| •    | 1 1/4 - 3/4          | 770 245 126   | 770 245 226        | 0  | 60  | 57        | 46        |
| •    | 1 1/4 - 1            | 770 245 127   | 770 245 227        | 0  | 50  | 57        | 46        |
| •    | 1 1/2 - 3/4          | 770 245 128   | 770 245 228        | 0  | 20  | 59        | 50        |
| •    | 1 1/2 - 1            | 770 245 129   | 770 245 229        | 0  | 50  | 59        | 50        |
| •    | 1 1/2 - 1 1/4        | 770 245 130   | 770 245 230        | 0  | 40  | 59        | 50        |
| •    | 2 - 1                | 770 245 131   | 770 245 231        | 0  | 25  | 68        | 65        |
| •    | 2 - 1 1/4            | 770 245 132   | 770 245 232        | 0  | 25  | 68        | 65        |
| •    | 2 - 1 1/2            | 770 245 133   | 770 245 233        | 0  | 20  | 68        | 65        |
| -    | 2 1/2 - 1 1/2        | 770 245 134   | 770 245 234        | 0  | 15  | 75        | 80        |
| •    | 2 1/2 - 2            | 770 245 135   | 770 245 235        | 0  | 10  | 75        | 80        |
| •    | 3 - 2                | 770 245 136   | 770 245 236        | 0  | 8   | 83        | 95        |
| •    | 3 - 2 1/2            | 770 245 137   | 770 245 237        | 0  | 8   | 83        | 95        |
| -    | 4 - 3                | 770 245 138   | 770 245 238        | 0  | 12  | 96        | 120       |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>