

- | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Unique identification code of the product-type: | Solid fuel fireplace without hot water supply
EN 13240:2001, EN 13240:2001/A2:2004
EN 13240:2001/A2:2004/AC:2006
EN 13240:2001/AC:2006
LARA |
| 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | Serial № (see rating label on the product). |
| 3. Intendent use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Freestanding fireplace for intermittent burning and space heating in buildings, with firedoors closed |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11 (5) | AD Metal industry «Alfa-plam» -Vranje
Radnička 1- 17500 Vranje SRBIJA
017-421121 - e-mail: firma@alfaplam.rs |
| 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2): | |
| 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: | System 3 |
| 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: | ACTECO s.r.l
Via Amman,41-33084 CORDENONS -Italy
Test report: n.0024-13FA |
| 8. Declared performance: | |

Harmonized technical specification	EN 13240:2001; EN 13240:2001/A2:2004
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm Back floor = 150 Lateral = 300 Front = 850
Risk of burning fuel falling out	Pass
Emission of combustion products	CO (0.23%) wood dust (-mg/m ³) NOx (-mg/m ³) CxHx (-mg/m ³)
Surface temperature	Pass (operating tool)
Electrical safety	NPD
Cleanability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T(-°C) wood
Mechanical resistance (to carry a chimney / flue)	NPD
Thermal output	
Nominal heat output	8,2 kW wood
Room heating output	8,2 kW wood
Water heating output	- kW
Energy efficiency	η(75,3%) wood

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

14.10.2013
 Vranje



Goran Kostić, general manager

Goran Kostić