

## OTDR-uri Tribreer

Model	Lungimi de unda[nm]	Gama dinamica[dB]	Funcții				Aplicații		Tip rețea			Funcții adiționale
			VFL	PW	OLS	VIP	Depanare	Certificare	P2P	PON	Live	
TB-620	1310/1550	22/20	•	•	•		✓		▪			Ecran color 3,2 inch
TB-700	1310/1550	22/20	•	•	•		✓		▪			Testare cabluri torsadate, ecran 3,5 inch
TB-720-B	1310/1550	32/30	•	•	•		✓		▪			Testare cabluri torsadate, ecran senzitiv 3,5 inch
TB-720-M	850/1300	20/24	•	•	•		✓		▪			Testare cabluri torsadate, ecran senzitiv 3,5 inch
TB-720-P1	1310/1550/1625	32/30/30	•	•	•		✓		▪	▪	▪	Testare cabluri torsadate, ecran senzitiv 3,5 inch, masoara prin splitter 1x 8
AOR502A	1310/1550	40/38	•	•	•	•	✓	✓	▪	▪		Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502M1	850/1300	26/26	•	•	•	•	✓	✓	▪			Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502B	1310/1550	43/41	•	•	•	•	✓	✓	▪	▪		Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502PA	1310/1550/1625	38/36/36	•	•	•	•	✓	✓	▪	▪	▪	Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502P1	1310/1550/1625	40/38/36	•	•	•	•	✓	✓	▪	▪	▪	Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502A-M1	850/1300/1310/1550	26/26/40/38	•	•	•	•	✓	✓	▪	▪		Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502C	1310/1550	45/43	•	•	•	•	✓	✓	▪	▪		Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502P3	1310/1550/1625	43/41/40	•	•	•	•	✓	✓	▪	▪	▪	Monitorizare nivel putere, ecran senzitiv 7 inch
AOR502P4	1310/1550/1625	45/43/43	•	•	•	•	✓	✓	▪	▪	▪	Monitorizare nivel putere, ecran senzitiv 7 inch, masoara prin splittere 1 x 64

Note:

VFL- visual fault locator – locator vizual de defecte

PW- powermeter – wattmetru optic

OLS – optical light source – sursa lumina infrarosu

VIP – video probe – functie inspectie conectori optici