

ARD-MINIPROX Card reader, HIDprox, mullion

PROXIMITY Reader



- Reader with beeper and multicolored LED display
- ► Plastic-coated for indoor and outdoor mounting
- ► Supports PROX cards
- ► Supports Wiegand interface

The ARD-MINIPROX proximity reader is a non-contact access control reader.

The reader operates through a Wiegand interface. This compact reader is suitable for wall and mullion mounting.

The reader supports PROX cards.

A multicolored LED and a beeper give a clear feedback to the user during operation.

The reader is IP55 rated and appropriate for indoor and outdoor use.

Regulatory information

Region	Regulatory compliance/quality marks
Global	RoHS
Russia	EAC
Region Regulatory compliance/quality marks	
Europe	CE

Installation/configuration notes

The ARD-MINIPROX proximity reader can be connected to the controller through the Wiegand interface and can be implemented in the BIS or AMS.

The reader supports cards with PROX technology.

Parts included

Quantit y	Component
1	Reader body with board
1	Mounting material
1	Installation guide

Technical specifications

Connectivity

Reader interfaces	Wiegand
Electrical	
Operating voltage (VDC)	5 VDC - 16 VDC

Environmental

Usage	Indoor; Outdoor
Operating temperature (°C)	-30 °C − 65 °C
Operating relative humidity, non- condensing (%)	10% - 95%
IP rating	IP55

ACD-PROXCARDII Clamshell card, HIDprox, 26 bit,

Order number ACD-PROXCARDII | 4.998.142.129

Packing information: 50 cards/ each unit

50pcs

Mechanical

Dimension (H x W x D) (mm)	43 mm x 152 mm x 25.40 mm
Material	Plastic
Color	Black
Weight (g)	99 g

Operation

Optical indication	LED
LED indication	Multi-color
Audible indication	Yes
Keypad	No
Reading format	HID Prox
Read range (cm)	7 cm - 13 cm
Wireless transmission frequency	125 kHz

Ordering information

ARD-MINIPROX Card reader, HIDprox, mullion

Small reader (for door jambs) with beeper and multicolored LED display.

Order number ARD-MINIPROX | 4.998.141.822

Accessories

D8236-10 Clamshell card, HIDprox, 26 bit, 10pcs

Randomly-coded proximity card that is Wiegand 26-bit. Each package contains ten cards.

Order number D8236-10 | 4.998.800.114

D8236KF-10 Keyfob, HIDprox, 26bit, 10pcs

Randomly-coded, black/gray, plastic, Wiegand 26-bit token. Attaches to a key chain. Each package contains ten tokens.

Order number **D8236KF-10 | F.01U.013.672**

D8236TG-10 Keyfob, HIDprox, 26bit, 10pcs

Randomly-coded, gray, plastic, Wiegand 26-bit adhesive tag. Attaches to non-metallic surfaces. Each package contains ten tags.

Order number **D8236TG-10 | 4.998.155.062**

ACD-ISO CARD Card, HIDprox, 26 bit, 50pcs Packing information: 50 cards/ each unit

Order number ACD-ISO CARD | 4.998.142.128

Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 www.boschsecurity.com/xc/en/contact

5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 www.boschsecurity.com/xc/en/contact/ www.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Tel.: +49 (0)89 6290 0 Fax:+49 (0)89 6290 1020 de.securitysystems@bosch.com www.boschsecurity.com

North America:

North America: Bosch Security Systems, LLC 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2809 www.boschsecurity.com/xc/en/contact/ www.boschsecurity.com