

ARCHITECT®

THE MOST AWARDED LINE OF ACCESS CONTROL READERS



DESIGNED & MADE IN FRANCE

SMARTER SECURITY ANSWERS



Every now and again, things come along that completely transform our way of thinking, creating new benchmarks and challenging our well-worn concepts.

With its innovative range of Architect® readers, STid has created the perfect blend of high security and upgradability. This is the first modular range of secure RFID, NFC (HCE) and Bluetooth® readers offering both flexibility and simplicity.

Architect® readers are built on an intelligent RFID core (Bluetooth® optional), to which various interchangeable modules can be connected: card reader, keypad, touch screen, biometric fingerprint sensor, 1D & 2D code reader (QR Code) and 125 kHz reader, facilitating seamless technological migrations.



The most awarded access control reader around the world

ARCHITECT®

DESIGN & CUSTOMIZABLE

Let your imagination flow

VANDAL-PROOF

Standing the test of time

HIGH SECURITY

Easy access to high security

MULTI-TECHNOLOGY

Make your migration simple



SCALABILITY AND MODULARITY

Create your own scalable configuration

Intuitive and dynamic, the Architect® range is made up of 6 interchangeable modules that can be easily connected to an intelligent RFID core (Bluetooth® optional).

Adapted to offer the best solution in all situations, this concept provides the ability to upgrade all the features and security levels of your inventory of readers.

This easy and cost saving modular approach lets you manage the security of your access points autonomously.

The concept offers a greater degree of availability and services, while optimizing your inventory by reducing the number of parts needed by 40%.



EASY ACCESS TO HIGH SECURITY

STid is the first RFID manufacturer to have received First Level Security Certification (CSPN)* and to offer access solutions compliant with European regulations on personal data protection (GDPR).

It's a recognition of our unique know-how, the technological and security expertise that are implemented in your access architectures, whether new or existing.

Keep control and remain fully independent in your access control management.

All public encryption algorithms can be used (3DES, AES, RSA, SHA...), which are recommended by official data security agencies (such as the French national agency ANSSI).

The Architect® readers use the latest MIFARE® DESFire® EV3 contactless chips with new data security mechanisms:

- **Secure Messaging EV2 / EV3**: secure transaction method based on AES-128
- **Proximity Check**: enhanced protection against relay attacks.

MAKE YOUR MIGRATION SIMPLE

Architect® facilitates the management of complex multi-site configurations, evolutions, and technological migrations towards the highest levels of security.

The reader line supports the widest range of credential technologies:

- **MIFARE®** Classic EV1®, Ultralight® & Ultralight C®, Plus® & Plus® EV1, DESFire® 256, EV1, EV2 & EV3 credentials. Reading of the CSN of iCLASS™** cards.
- **STid Mobile ID®** virtual cards in NFC and/or Bluetooth®. With Bluetooth® technology, choose your preferred identification modes to make your access control both secure and much more intuitive.

STID MOBILE ID



CARD MODE



HAND-FREE MODE



REMOTE MODE



VOICE COMMAND



SLIDE MODE



TAP TAP MODE

- **Apple Wallet™**: the readers support Apple's Enhanced Contactless Polling (ECP v2.0) for all access control applications with an iPhone or Apple Watch using NFC. With Express Mode, users are spared the need to unlock their devices to use their card in Apple Wallet™. Even when the device runs out of battery charge, they can still gain access to their office for up to five hours thanks to Power Reserve.
- **Legacy 125 kHz technologies**: EM®, HID Proximity®, AWID®, IOPROX®, INDALA® 26 & 27 bits depending on the chosen Prox module.

Architect® is also available in LEGIC® version.

Best Market Self-protection

— The patented tamper protection system protects sensitive data and gives the possibility to delete the authentication keys. Unlike the current solutions on the market, the reliability of the accelerometer-based technology avoids it being outsmarted.

The Architect® Blue range uses an EAL5+ certified crypto processor to encrypt your data.

* Certified reader: LXSW33EPH57AD1 - Certificate ANSSI-CSPN-2013/03 of March 19, 2013 and October 24, 2013

** Our readers only read the serial number / UID of the iCLASS™ ISO14443A chip. They do not read HID Global's iCLASS™ cryptographic protections.

LET YOUR IMAGINATION FLOW

A signature reflects personal style choices. The design of Architect® readers is immediately recognizable, with a dynamic and elegant style, featuring clean, pure lines. The Architect® range is elegant day or night thanks to its set of multi-colored, high-intensity LEDs.

STid offers a range of customization options to tailor your reader to your corporate identity and integrate it fully into its installation environment.

COMMUNICATION VECTOR



Print your logo using digital UV or pad printing

SMART LIGHTING

Global vision multi-angle system
Customization of the LEDs
(360 colors)

YOUR READER IS A PIECE OF ART

Latest customization technology named Skin Effect for a spectacular experience



THE COLOR OF YOUR BUSINESS

Select your favorite casing color



Standard



On request

SPECIFICATIONS

READER	MIFARE® version	BLUETOOTH® version	LEGIC® version
Operating frequency / Standards	13.56 MHz - ISO14443 A & B, ISO18092 (NFC) Bluetooth® (according version)		13.56 MHz - ISO14443A, ISO15693 LEGIC® RF Standard
Supported credential technologies	13.56 MHz MIFARE Ultralight® & Ultralight® C, MIFARE® Classic & Classic EV1, MIFARE Plus® & Plus® EV1, MIFARE® DESFire® 256, EV1, EV2 & EV3, SMART MX, CPS3, iCLASS™** (CSN only), PicoPass® (CSN only) STid Mobile ID® virtual cards (NFC and/or Bluetooth®), Apple Access stored in Apple Wallet™, Orange Pack ID		LEGIC® Advant & Prime / CSN MIFARE® Ultralight® & Ultralight® C, Classic & Classic EV1, Plus® & Plus® EV1, DESFire® 256, EV1 & EV2, iCLASS™** PicoPass®, Inside®
Functions	Read-only CSN, pre-configured (Easyline - PC2), and secure (file, sector) / Protocol-driven (read-write)		Read-only CSN or secure (segment) / Protocol-driven (read-write)
Communication interfaces & protocols	TTL Clock&Data (ISO2) or Wiegand (encrypted option - Sx1) output RS485 output (encrypted option - Sx3) with secure communication protocols SSCP® V1 & V2; OSDP™ V1 (plain communication) and V2 (SCP secure communication) RS232 output available in MIFARE® version only EasySecure compatible interface / Transparent interfaces in MIFARE® version only		TTL / RS232: Clock&Data (ISO2), Wiegand or RS232 (SSCP® protocol V1) TTL / RS485: Clock&Data (ISO2), Wiegand or RS485 (SSCP® protocol V1)
Reading distances*	Up to 8 cm / 3.15" with a DESFire® EV3 card	Up to 8 cm / 3.15" with a DESFire® EV3 card 0 - 20 m / 65.6 ft depending the Bluetooth® mode	Up to 8 cm / 3.15" with a LEGIC® Prime card Up to 6 cm / 2.36" with a LEGIC® Advant card
Secure EAL5+ storage	-	Yes	-
Light indicators	2 RGB LEDs - 360 colors Configuration by card (standard or virtual with STid Settings application), software or external command (0V) according to the interface		2 RGB LEDs - 360 colors Software-configuration or External command (0V)
Audio indicator	Internal buzzer with adjustable intensity Configuration by card (standard or virtual with STid Settings application), software or external command (0V) according to the interface		Internal buzzer Software-configuration or External command (0V)
Power requirement	Max. 130 mA / 12 VDC	Max. 150 mA / 12 VDC	Max. 130 mA / 12 VDC
Power Supply	7 VDC to 28 VDC		
Connections	10-pin plug-in connector (5 mm / 0.2") 2-pin plug-in connector (5 mm / 0.2"): O / F contact - Tamper detection signal		
Material	ABS-PC UL-V0 (black) / ASA-PC-UL-V0 UV (white)		
Dimensions (h x w x d)	107 x 80 x 26 mm / 4.21" x 3.15" x 1.02"		
Operating temperatures	- 30°C to + 70°C / - 22°F to + 158°F / Humidity: 0 - 95%		
Tamper switch	Accelerometer-based tamper detection system with key deletion option (patented) and/or message to the controller		
Resistance / Protection	IP65 Level (excluding connectors) / UL294 Outdoor certified - Weather-resistant with dust and water-proof electronics (CEI NF EN 61086 homologation) IK10 certified and reinforced vandal-proof structure		
Mounting	Wall mount / Flush mount (European & American) Compatible with any surfaces and metal walls		
Certifications	CE (Europe), FCC (USA), IC / ISED (Canada), UKCA (United Kingdom), RCM (Australia, New Zealand), BIS (India), Morocco (ANRT), UL, UL294 Indoor & Outdoor, RoHS		CE (Europe)

KEYPAD FEATURES

Keypad	Capacitive Touch keypad - 12 configurable backlit keys - Configuration by card (standard or virtual with STid Settings application) or software according to the interface	Capacitive touch keypad 12 configurable backlit keys - Activated / deactivated by software
Dimensions (h x w x d)	107 x 80 x 26 mm / 4.21" x 3.15" x 1.02"	
Operating temperatures	- 30°C to + 70°C / - 22°F to + 158°F / Humidity: 0 - 95%	
Resistance / Protection	IP65 Level (excluding connectors) / UL294 Outdoor Certified - Weather-resistant with dust and water-proof electronics (CEI NF EN 61086 homologation) IK08 certified and reinforced vandal-proof structure / High resistant laser marking of keys	

TOUCHSCREEN FEATURES

Type	Color touchscreen and keypad
Touchscreen size	2.8" - 240 x 320 pixels
Touch keypad / Display	12 keys - Standard or scramble pad function / Display of images & texts / 4 function buttons in OSDP™
Dimensions (h x w x d)	128 x 80 x 31 mm / 5.04" x 3.15" x 1.22"
Operating temperatures	- 20°C to + 70°C / - 4°F to + 158°F / Humidity: 0 - 95%
Resistance	IP65 level (excluding connectors) - Weather-resistant with dust and water-proof electronics (CEI NF EN 61086 homologation)
Doorbell function	Activated / deactivated according to your configuration

BIOMETRIC FEATURES

Fingerprint sensor	Optical (MorphoSmart™)
Identification time	≤ 1 second
Anti-fraud functions	Detection of dead fingers, false fingers and fingers under stress
Collecting area	14 x 22 mm / 0.55" x 0.87"
Dimensions (h x w x d)	60 x 80 x 62 mm / 2.36" x 3.15" x 2.44" (biometric module only)
Operating temperatures	- 10°C to + 50°C / +14°F to + 122°F / Humidity: 0 - 95%
Resistance	IP65 Level - Weather-resistant with dust and water-proof electronics

125 KHZ PROX FEATURES

125 kHz card reader	SE8 version: EM42xx / EM4x50 / Wiegand formats 26, 34, 35 and 37 bits / Nedap / Crosspoint. SE8M version: EM42xx / EM4x50; HID Proximity®, INDALA® (Wiegand 26 & 27 bits); IOPROX®; AWID®
Dimensions (h x w x d)	38.99 x 79.93 x 25.7 mm / 1.49" x 3.11" x 0.98" (module only)
Operating temperatures	- 30°C to + 70°C / - 22°F to + 158°F / Humidity: 0 - 95%
Resistance / Protection	IP65 level (excluding connectors) / UL294 Outdoor Certified - Weather-resistant with dust and water-proof electronics (CEI NF EN 61086 homologation) IK10 certified and reinforced vandal-proof structure

QR CODE / 1D & 2D CODE FEATURES

1D & 2D code technologies	QR Code / Micro QR Code, Datamatrix, Aztec, Code 128
Dimensions (h x w x d)	62.42 x 80 x 35,74 mm / 2.45" x 3.14" x 1.38" (module only)
Operating temperatures	- 30°C to + 60°C / - 22°F to + 140°F / Humidity: 5 - 90%
Resistance / Protection	IP65 Level (excluding connectors) - Weather-resistant with dust and water-proof electronics (CEI NF EN 61086 homologation). IK08 certified and reinforced vandal-proof structure

FOCUS



Easy multi-mode configuration: card⁽¹⁾, smartphone⁽²⁾ and secure connection.



Compliant with the new European regulation on personal data protection (GDPR).



Readers fully compatible with the High Security SSCP® - Secure & Smart Communication Protocol for certified solutions.



Readers fully compatible with the SIA Open Supervised Device Protocol - OSDP™ V1 and V2 (according model).

(1) MIFARE® version, (2) Bluetooth® version

*Caution: information about the distance of communication: measured from the centre of the antenna, depending on the type of credential, size of the credential, operating environment of the reader, power supply voltage and reading functions (secure reading).

** Our readers only read the serial number / UID of the iCLASS™ ISO14443A chip. They do not read HID Global's iCLASS™ cryptographic protections.



SMARTER SECURITY ANSWERS



Headquarters / EMEA

13850 Gréasque, France
Tel.: +33 (0)4 42 12 60 60

PARIS-IDF Office

92290 Châtenay-Malabry, France
Tel.: +33 (0)1 43 50 11 43

STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK
Tel.: +44 (0) 192 621 7884

NORTH AMERICA Office

Irving, Texas 75063-2670, USA
Tel.: +1 877 894 9135

LATINO AMERICA Office

Cuauhtémoc, 06600 CDMX, México
Tel.: +52 (55) 5256 4706

MIDDLE EAST Office

Dubai Digital Park, DSO, UAE
Tel.: +971 521 863 656

info@stid.com
www.stid-security.com

Legal statements: STid, SSCP®, STid Mobile ID® and Architect® are trademarks of STid SAS. Apple Wallet™ is registered trademark of Apple. QR Code is registered trademark of DENSO WAVE INCORPORATED. All other trademarks are property of their respective owners. All rights reserved. This document is the exclusive property of STid. STid reserves the right to stop any product or service for any reason and without any liability. Noncontractual photographs.

© STid 2024, all right reserved / Broch_Architect-V10.00_US