



universal duo

TRANCEIVER & REPEATER

KSI2600001.310



DATASHEET

INTRODUCTION

The bi-directional universal receiver **duo** univ allows the use of wireless peripherals of Ksenia Security with any control panel or similar devices: this installation is possible thanks to 8 programmable outputs present on the device. The number of outputs can be increased up to 18 using auxi or auxi-relay modules.

TECHNICAL DATA

- **Power:** 13,8 Vdc
- **Consumption:** max 50mA
- **Operative Frequency:** 868 MHz Band
- **Range in open air:** up to 400 m
- **Max. WLS Device Nr.:** 32 Devices
- **Wireless Zones:** max 96
- **Operative Temperature:** from +5°C to +40 °C
- **Dimensions:** 140 x 100 x 28 mm (L x H x P)

HOW TO ORDER

KS12600001.310 - universal duo

ACCESSORIES

KS17302000.010 - Plastic box "slim" version

PARTS INCLUDED

- 1 Transceiver / Repeater universal duo(PCBA)
- 1 Slim Case with screw
- 1 Quick Installation Guide IT/EN/FR



DATASHEET

ENVIRONMENT PROTECTION

universal duo has been designed and manufactured with the following features to reduce environmental impact:

- PVC-free
- Halogen-free laminates and printed circuits unleaded
- low absorption
- Packing made for the most part with recycled fibers and materials from renewable sources

