

DM3010R-IP

3000 Series intelligent addressable manual call point, weatherproof

General

The DM3000 Series is an intelligent range of addressable manual call points. The DM3010R-IP is a weatherproof, red, single action MCP with a House-on-Fire functional indication. It is delivered complete with resettable element, test connector and test key. Multiple optional accessories are available to facilitate most in- and outdoor installation requirements.

Aesthetics

This weatherproof single action MCP is a standard profile MCP suitable for surface mount installations. It is supplied with a colour matched weatherproof back box. With its designer dual, tricolour LEDs it offers 180°, clear local indication of its operational status, even from a side view. The clean face of the MCP is further enhanced by a front access & test key facility.

Installation & maintenance friendly

The front facing access for an aesthetically matching test key allows unhindered access regardless of the installation location. The MCP key doubles as a test and disassembly tool allowing removal of the MCP front cover without the need for additional tools.

Compatibility

The DM3000 range may be used on compatible Aritech fire systems. They can in many cases be deployed into existing systems without CIE configuration changes.



Details

- Reliable single action manual call point for surface mounting
- Dual, tri-colour status indicators offers 180° alarm visibility
- Tamper resistant design with resettable or frangible element
- Unobtrusive front facing test facility
- Standard mounting options facilitates easy retrofitting to existing installations
- Back box with rear, top and bottom cable entry
- Screen connection terminal in the back box for electrically noisy installations
- Pluggable connector with link through facility for ease of installation and pre-commissioning testing
- An alarm flag on the face of the manual call point allows alarm indication even without alarm LEDs
- Fast, no-tools-required maintenance using the test key
- Up to 128 devices supported per loop

DM3010R-IP

3000 Series intelligent addressable manual call point, weatherproof

Technical specifications

General

Status indication	Dual LEDs, Alarm (red constant), Isolated (yellow constant), Fault (yellow blinking), Communication (green blinking)
User interface	LEDs, Alarm Flag
Compatibility	Aritech fire systems
Connectivity	2-wire loop

Electrical

Operating voltage	17 to 38 VDC
Current consumption	180 µA (Quiescent) 2.8 mA (Alarm)
Cable specification	0.404 to 2.05 mm
No. of cable cores	2
Terminals	4 (A+/A-;B+/B-)

Detection

Detection principle	Push button/switch
Installation height	Determined by local regulation

Physical

Physical dimensions	108 x 108 x 69 mm
Net weight	267 g (w/ back box)
Cable entries	3 x threaded MK20
Functional marking	House on Fire

Environmental


Operating temperature	-25 to +72°C
Storage temperature	-25 to +72°C
Relative humidity	10 to 95% noncondensing
IP rating	IP67

Regulatory

Standards	EN54:11
-----------	---------

Compatible products

Category	Reference	Description
Detection device	N-MC-FC	MCP accessory, intelligent Manual Call Point flip cover
Detection device	N-MC-FE	MCP accessory, intelligent manual call point frangible element



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 March 2024 - 15:50