

# DMN700Y

## Manual Callpoint, Flush Mount, Yellow, Free Contact, Break Glass

### General

---

The DMN700R100-KITR is a red manual call point for surface mount applications. It has an internal 100 ohm series resistor and free contact. It is supplied complete with a resettable element, test key and surface mount box.

### Installation

---

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

### Options and approvals

---

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard



### Details

---

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

# DMN700Y

## Manual Callpoint, Flush Mount, Yellow, Free Contact, Break Glass

### Technical specifications

---

#### Isolation

Series resistance	NA
-------------------	----

---

#### Physical

Net weight	110 g
Colour	Yellow
Mounting type	Recessed mount
Material (body)	PC / ABS

---

#### Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP24D

---

#### Cable Termination

0.5 to 2.5 mm <sup>2</sup>
----------------------------

---

#### Max. contact rating (resistive load)

2 A @ 30 VDC
--------------

---

#### Compatible products

Category	Reference	Description
Detection device	DM711	
Detection device	DM715	EN54 Universal MCP Glass (Without Branding)
Detection device	DMN782	Hinged Transparent MCP Protection Cover
Detection device	DMN784	Replacement Test Key For Manual Call Points (10 Pack)
Detection device	DMN789	

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 26 April 2024 - 10:07